

LOCTITE®



Loctite® 5075 Insulating & Sealing Wrap

Product features:

- Service temperature range -54°C to 260°C
- Tensile shear strength 5N/mm²
- UV resistant
- Resistant to salt water, fuels and acids
- Available in red or black

Your benefits:

- Non-sticky, self fusing multipurpose wrap
- Stretches 3-times its length
- Seals instantly
- Withstands extreme conditions

Henkel Excellence is our Passion

Loctite® 5075

Insulating & Sealing Wrap



Typical applications

Industrial

- Repair seals for rigid and flexible pipes, ducts, hoses, vents, etc.
- Electrical insulation for connectors, terminals, motors, etc.
- Wrapping for tool handles



Automotive

- Automotive repair tape
- Emergency radiator hose repairs
- Automotive harness wrapping
- Jumper cable grip/insulation
- Vibration protection for hoses & pipes
- Temporary hose clamp applications



Marine

- Boat rigging wrap
- Marine exhaust repairs
- Boat wiring protection
- Coolant line repairs
- Wrapping of wire rope "ends"
- Sailboard wishbones rewrapping
- Underwater use



Henkel Limited

Wood Lane End, Hemel Hempstead,
Hertfordshire HP2 4RQ
Technical Helpline Phone: 01442 278100
Fax: 01442 278071
E-mail: technicalservice.loctite@henkel.com
www.loctite.co.uk