

# LOCTITE®

## Loctite® 55 Pipe Sealing Cord

*Adjustable - Faster - Safer - Easier*

- Allows fittings to be “backed-off” for alignment without fear of leakage
- Suitable for hot and cold water, potable water, gas, LPG and compressed air




Henkel



# Loctite 55 Pipe Sealing Cord

**4 easy steps....**



**....to a better joint**

## A better joint for pipe systems

Loctite 55 Pipe Sealing Cord is a new, faster, cleaner, more versatile pipe sealant which out-dates traditional tapes and hemp/paste combinations. It therefore enables the improvements required of today's pipe systems. Naturally, it complies with all latest regulations.

- **Loctite 55**  
replaces tapes, hemp and pastes
- **Loctite 55**  
seals pipe threads up to 4"
- **Loctite 55**  
has UK and European approvals for potable water and gas
- **Loctite 55**  
seals against hot or cold water, gas, LPG and compressed air

## New technology, same traditional skills

You don't need special training to use Loctite 55. Use your old skills to apply the new technology to get an instant seal. Wrap the sealing cord around the male threads, use the recommended number of turns for the size of thread - and assemble. That's all there is to a leak-proof joint.

- **Loctite 55**  
allows fittings to be "backed-off" for alignment without fear of leakage
- **Loctite 55**  
gives the bonus of speed, cleanliness and an assured first time seal that will not require return visits
- **Loctite 55**  
can be safely used on cast iron, steel, brass, copper, chrome, nickel-plated and galvanised surfaces, stainless steel and plastic parts

A single reel of Loctite 55 will seal:

Thread size	1/2"	3/4"	1"
Approx. number of joints - 150 metre pack	385	260	180
Approx. number of joints - 50 metre pack	130	85	60

*Loctite 55 is easily applied directly from these handy, pocket-sized, protective containers with a built-in cutter*

**Available in 150 and 50 metre packs**



Henkel Loctite Adhesives Limited  
Technologies House, Wood Lane End,  
Hemel Hempstead, Hertfordshire HP2 4RQ  
Technical Helpline Phone: 01442 278100  
Fax: 01442 278071  
E-mail: [technicalservice.loctite@uk.henkel.com](mailto:technicalservice.loctite@uk.henkel.com)  
[www.loctite.co.uk](http://www.loctite.co.uk)

Available from: