

# LOCTITE®



## Ready-to-use Flange Sealants

Multi-Purpose

Long-term proven sealant technology from Henkel – the perfect gasket solution to meet all your requirements.


- **Loctite® 5980** perfect for flanges with permanent oil contact
- **Loctite® 5660** long-term resistance to water & glycol
- **Loctite® 5990** excellent in high temperature environments



**New Packaging**

### Main Benefits

- For all kind of flanges including metals and plastics as well as combinations of both
- Safety label-free formulation
- Can replace pre-cut paper or cork gaskets
- Neutral curing
- Low odour
- Non-corrosive
- Long-term resistance
- Ready-to-use Can



The resealable “Ready-to-use Can” requires no additional tools and allows dispensing with extra accuracy and adjustable flow rate.

**Henkel** Excellence is our Passion

# Ready-to-use Flange Sealants

## Multi-Purpose



These highly elastic sealants, with excellent adhesive strength to most surfaces, fulfill all your repair and maintenance requirements. Based on long term proven sealant technology this new Gasket line will answer all your needs!

### Improve your Health & Safety Conditions with Henkel

Loctite® ensures durable gasketing to prevent leakage of hazardous liquids. Health and Safety also means our Premium High Performance Silicones enable energy neutral cure and safe handling without any smell. Finally, this safety label free Gasket Line delivers easy and Health & Safety-friendly handling for operators with no compromise on performance!

### Specific Needs – Specific Solutions



#### Loctite® 5980

Premium high performance silicone black

For flanges exposed to permanent oil contact.



| Pack size               | IDH No. |
|-------------------------|---------|
| Blister card 40 ml      | 1718284 |
| Tube 100 ml             | 1717857 |
| Ready-to-use can 200 ml | 1299784 |
| Cartridge 300 ml        | 1716829 |



#### Loctite® 5660

Premium high performance silicone grey

For flanges with long term water or glycol resistance.



| Pack size               | IDH No. |
|-------------------------|---------|
| Blister card 40 ml      | 1718240 |
| Tube 100 ml             | 1717638 |
| Ready-to-use can 200 ml | 1721267 |
| Cartridge 300 ml        | 1717493 |



#### Loctite® 5990

Premium high performance silicone copper

For flanges exposed to high temperatures (up to 300°C).



| Pack size               | IDH No. |
|-------------------------|---------|
| Blister card 40 ml      | 1716588 |
| Tube 100 ml             | 1704658 |
| Ready-to-use can 200 ml | 1721241 |
| Cartridge 300 ml        | 1696686 |

### Application Areas

Sealing of metal and plastic flanges, e.g. oil pan, differential cover, valve cover, transmission pan, water pump, timing chain cover, thermostat, cooling system, transmission cover, inlet manifold.

#### Henkel Limited

Technologies House, Wood Lane End,  
Hemel Hempstead, Hertfordshire HP2 4RQ  
Technical Helpline Phone: 01442 278100  
Fax: 01442 278071  
E-mail: [technicalservice.loctite@henkel.com](mailto:technicalservice.loctite@henkel.com)  
[www.loctite.co.uk](http://www.loctite.co.uk)