TYGRIS MRO Solutions **Cleaning Lubricating Protecting** TWGRIS Chassis Grease 000 MGRIS **High Power** MGRIS TMGRIS GalvShield

Our comprehensive range of TYGRIS MRO Solutions

are designed to deliver performance, reliability, efficiency, confidence and convenience... guaranteed 4Life!

With infinite appeal, every product is designed to do the job, first time, every time, helping TYGRIS to continue to fulfil the Cleaning, Lubricating and Protecting needs of industry, as we have done so since 1971.

Make TYGRIS your #1 choice for all your Cleaning, Lubricating and Protecting needs!

There is a better way...

Index

Section 1 Spray Solutions ** Cleaning Degreasing 5 Lubricating Maintaining 18 Protecting Finishing 32 Section 2 Bulk Lubrication 38

58





Spray Solutions

Our comprehensive range of TYGRIS aerosols

are designed to deliver performance, reliability, efficiency, confidence and convenience in easy-to-use spray formulations.

With infinite appeal, every product is designed to do the job, first time, every time, helping TYGRIS to continue to fulfil the Cleaning, Lubricating and Protecting needs of industry, as we have done so since 1971.





Cleaning Degreasing

Our TYGRIS range of powerful cleaning aerosols deliver effective solutions for everyday, essential and challenging cleaning tasks.

Sector guide -



Automotive



Electrical



Food Area



Industrial Maintenance & Operation



Janitorial & Hygiene



Plastic Moulding



The TYGRIS Aerosol Can

Every TYGRIS can has been designed with the user in mind, combining clear and concise information with an innovative range of technical application illustrations for ease of identification and effective product differentiation.

Clear 'Easy-Read' product title

Product description summary

4Life Guarantee ensures complete peace of mind

'Quick glance' diagrams for faster product recognition

TYGRIS product code

Detailed product description to assist in choosing the right product for the job

Specific directions for use provide the 'know how' when applying the products to achieve best results

Helpful 'tips for use' make the difference to getting the most out of a product

All cans are barcoded to support stock tracking and scanning

Legally sized safety & product hazard information



...more than you'd expect!





Dashboard Renovator

Cleans and polishes leaving a pleasant fragrance

R199	Cherry	400m
R200	Apple	400m
R205	Cranberry	400m
R206	Lemon	400ml

TYGRIS Dashboard Renovator is a light duty, pleasantly fragranced cleaner and polish for internal plastics and trim in automotive applications. It cleans and shines dashboards, fascias and other interior panels, restoring to original appearance without the need for manual buffing. It is fast acting with nearly instantaneous evaporation.

Benefits:

- · Silicone based for good cleaning and finish
- Easy to use, no buffing required
- · Restores original appearance
- Fast acting and evaporation
- · Pleasant fragrance



Carburettor Cleaner

Cleans stubborn deposits and improves engine performance

R201 400ml

TYGRIS R201 is a strong solvent based cleaner used for the removal of oil, grease and stubborn gum deposits from carburettors and injection systems. Suitable also for cleaning brake parts and automatic chokes without dismantling in order to prevent stalling and to smooth out rough idling.

Benefits:

- Strong solvent for stubborn deposits
- · Dissolves grease and oil
- · Helps to restore engine performance
- Removes combustion deposits from nail qun mechanisms
- Safe for use with catalytic convertors and oxygen sensors



Brake and Clutch Cleaner

Non-staining fast evaporating cleaner for brakes and clutches

R202 400ml

TYGRIS R202 is a powerful cleaning fluid used to remove oil, grease, dirt and dust from brakes and clutches, aiding in the elimination of brake squeal and clutch slip caused by glazing and contamination. Can be used on many other surfaces as a powerful cleaning agent.

Benefits:

- · Colourless non-staining
- · Fast evaporating solvents
- Effective against grease, brake fluid, brake and clutch dust
- Can be used to remove tar spots from some surfaces
- Eliminates brake squeal and clutch slip



Engine Degreaser

Dissolves and emulsifies grease and oil for washing off

R203 400ml

TYGRIS R203 is a powerful, heavy duty emulsifiable solvent degreaser and de-waxer which simply sprays on and washes off, quickly removing oil, grease and tar deposits from engines and other surfaces.

Benefits:

- Use on any metallic surface
- · Removes grease, tar stains, oil, bitumen, waxes etc.
- · Dissolves and emulsifies for easy removal
- · Can be used on most plastic and painted surfaces
- Suitable for spot removal on concrete



Dashboard Cleaner Non-Silicone

Cleans and polishes leaving a pleasant fragrance

R270 400ml

TYGRIS R270 is a light duty, perfumed cleaner and polish for internal plastic, wood and veneered trim in automotive applications. It cleans as well as shines dashboards, fascias, and other interior panels, restoring to original appearance without the need for manual buffing. It is fast acting with nearly instantaneous evaporation and, being silicone-free, can be used in areas where painting and re-finishing takes place.

Benefits:

- Silicone-free for use in areas where re-finishing takes place
- Easy to use, no buffing required
- · Restores original appearance
- Fast acting and evaporation
- · Pleasant fragrance



High Power Brake Cleaner

Solvent based cleaner for brakes and clutches with very powerful spray action

R274 500ml

TYGRIS R274 is a high power spray cleaning fluid used to remove oil, grease, dirt and dust from brakes and clutches, aiding in the elimination of brake squeal and clutch slip caused by glazing and contamination. Can be used on many other surfaces as a powerful cleaning agent.

- · Very powerful spray
- Colourless non-staining
- Fast evaporating solvents
- Effective against grease, brake fluid, brake and clutch dust
- Can be used to remove tar spots from some surfaces
- Eliminates brake squeal and clutch slip



Industrial Cleaner Fast Drying

Fast drying solvent based cleaner which leaves no residue

R207 400ml

TYGRIS R207 is a fast drying industrial cleaner which is used to break down grease, dirt, oil and other workshop contaminants quickly and easily without the need of subsequent rinsing, saving time and maintaining a clean environment.

Benefits:

- · Powerful solvent cleaning
- Breaks down workshop contaminants quickly
- · Solvent evaporates quickly, leaving a clean surface
- Non-chlorinated
- · No need for rinsing leaves no residue



Solvent Tool & Electronics Cleaner

Medium to fast evaporating solvent cleaner

IS2 400ml

TYGRIS IS2 is a medium to fast evaporating light duty solvent cleaner for use on metallic and plastic surfaces, removing general grime, and also greases and oils in heavier duty applications. Can be used on electrical equipment once the supply has been isolated.

Benefit

- Reasonably fast evaporation rate
- · Leaves no residue
- · Effective in delicate applications
- May also be used for heavier duty cleaning
- Easy to use with integral directional nozzle
- · Removes stains, oil, grease, and printing inks



Electrical Cleaner

Fast evaporating non-corroding electrical cleaner

R235 400ml

TYGRIS R235 Electrical Cleaning Solvent is an alcohol based cleaning solvent designed for use in the electronics and switchgear industries and is suitable for cleaning most electrical apparatus. Safe to use with most plastics, it effectively cleans and degreases electrical contacts, circuit boards and print heads, leaving no residues.

Benefits:

- · Powerful, effective cleaner
- Removes stains, coatings, printing aids, oil, grease, dirt and most fluxes
- · Leaves no residue
- Controlled drving time
- Safe with most plastics and on delicate instruments
- · Does not cause corrosion of metals
- Low toxicity



Electro Clean

Fast evaporating cleaner for batteries and electrical components

IS20 400ml

TYGRIS IS20 is a very fast evaporating solvent cleaner for use on electrical components, making maintenance quick and safe on switchgear, fork lift electrics and where equipment will be used soon after this is carried out. Requiring no rinsing or cleaning off, grease and dirt are quickly and efficiently removed.

- Very fast evaporating
- · Non-conductive
- · Efficient removal of grease and dirt
- Requires no further processing
- · Safe on most plastics and painted surfaces





"TYGRIS products are covered by our TYGRIS

4Life Guarantee, providing 100% satisfaction for both our distributors and end-users alike."

Quality

Quality control is an important part of the process that all TYGRIS products go through to maintain consistent and reliable supply. Our ISO 9001: 2008 accreditation ensures that all procedures are carried out to recognised standards.

Environment

Environmental standards are respected. TYGRIS products are manufactured to ISO 14001 : 2004 accredited procedures minimising any impact to the environment throughout production processes.

Recycling

TYGRIS aerosol cans are made from steel tinplate or aluminium, both of which are fully recyclable.

Regulations

Up-to-date safety data and technical data is available on all products.



Fast Dry Solvent Cleaner

Fast drying solvent cleaner

Nonfood Compounds Program Listed K1 Registration Number: 139297

F400 400ml

TYGRIS F400 is a powerful, fast drying solvent designed to dissolve away all types of contaminant in the workshop quickly leaving no residue, eliminating the need of rinsing.

Benefits:

- K1 Registered
- · Powerfully removes all types of contaminant
- Fast drying
- · Leaves no residue
- Does not contain chlorinated solvents
- Temp. range: -20°C to +65°C
- 360° valve for inverted use



Electrical Cleaner

Fast drying electrical cleaner

Nonfood Compounds Program Listed K2 Registration Number: 139295

F406 400ml

TYGRIS F406 is a quick drying solvent cleaner used in food and clean environments for effective cleaning and degreasing of electrical components which, when dry, leaves no residue, so making for an efficient process without the added chore of wiping off dissolved dirt.

Benefits

- K2 registered for use in food environments
- Solvent dries off in approximately 1 minute
- · Leaves no residue
- Safe for use on most plastic or painted surfaces
- · Effectively removes grease and dirt



Stainless Steel Cleaner

Metal polish and cleaner

Nonfood Compounds Program Listed A7 Registration Number: 139296

F420 400ml

TYGRIS F420 is a cleaner and polish used for stainless steel, aluminium and chrome in food and non-food processing environments which leaves a protective coating to aid future cleaning.

Benefits:

- A7 registered for use in or around food processing environments
- · For use on metal surfaces
- Cleans and polishes in one action
- Restores surface to original lustre
- Non-abrasive will not scratch
- 360° valve for inverted use



Foaming Cleaner

Multi-surface foam cleaner

Nonfood Compounds Program Listed A1 Registration Number: 145234

F422 400ml

TYGRIS F422 is a multi-surface foam cleaner for use on all types of equipment and hard surfaces in the food processing industry with a foaming action to help it cling for longer contact and action time.

Benefits

- A1 Registered for use in food environments
- · For use on all hard surfaces
- Foaming action for longer contact time
- · Cuts through grease and grime effectively
- Gentle cleaning action will not scratch
- · Benign cleaning ingredients
- 360° valve for inverted use



Label Remover

Penetrates and dissolves adhesives

Nonfood Compounds Program Listed K3 Registration Number: 145233

F424 400ml

TYGRIS F424 is a solvent based blend for the removal of sticky labels from most substrates including many plastics, metals, rubbers, painted surfaces and other impervious materials, leaving no residues or markings.

- Dissolves gums and adhesives from self adhesive labels
- Suitable for most surfaces
- Leaves no residues
- · High penetrating power
- 360° valve for inverted use





Developed to clean tough stuff, the NEW IMPROVED TYGRIS OneWipe™ will clean almost anything!

BIGGER, STRONGER and THICKER than ever before, with 110 hand wipes in every TYGRIS tub, OneWipe™ remains the professional's choice to clean hands, tools and surfaces.



See page 17 for further product information





Micro Air Duster (Low GWP)

Non-flammable, inert air duster

R241 400ml

Designed to physically remove dust, dirt and other loose-adhering contaminants, where the use the wet chemical products would be prohibited or impractical, TYGRIS R241 is suitable for use on electrical / electronic devices and equipment commonly found at home, work or play. Ideal for removing dust and debris from those hard-toreach places.

Benefits:

- F-GASES II (EC) REGULATION 517/2014 Compliant Product. Low GWP (Global Warming Potential) with NO ozone depletion potential
- · Highly pressurised discharge for rapid and effective dust and debris removal
- Immediate evaporation
- Extension nozzle for accurate application and accessing difficult-to-reach areas



Glass & Mirror Cleaner

Non-abrasive cleaner and degreaser

R244 400ml

TYGRIS R244 is a specially formulated aqueous, alcohol based cleaner which gives streak free cleaning of glass and mirrors, plastic, stainless steel and chrome. It is powerful enough to remove nicotine, finger marks, insects, lipstick and much more, making it ideal for car valeters, hospitals, hotels, airports, jewellers, window installers and cleaning contractors.

Benefits:

- · Dries streak-free
- · Effective cleaning and degreasing
- Fast acting
- Low foaming
- Virtually residue free
- · Abrasive free
- Safe for use on all glass and plastic surfaces
- · High level of detergency will remove hair spray deposits, lipstick, nicotine etc.



Air Freshener

Fast and effective scented deodoriser

R248 Cranberry 400ml R249 Lemon 400ml

This powerful action air freshener clears unwanted odours and leaves a long-lasting freshness to large and small areas. Its dry formulation makes it safe for use in the home and is ideal for hospitals, care homes, changing rooms and community centres.

Benefits:

- Powerful deodoriser
- Use in large and small areas
- Dry formulation
- Long lasting



Super Power Air Freshener Cranberry

Cranberry scented power spray

R261 750ml

TYGRIS R261 is a powerful room air freshener that will counter unpleasant odours across large areas, replacing them with a fresh and pleasing aroma. Its extra power nozzle propels the product over a significant distance.

- High power nozzle for extra propulsion
- Pleasant cranberry aroma
- · Dry formulation for use in healthcare, community, leisure and commercial locations





Barrier Cream

Moisturising hand protection with bactericide

R250 400ml

TYGRIS R250 is a high quality water based blend of skin-care ingredients used to protect hands from industrial soiling. Contains conditioners, humectants and emollients to retain skin freshness and replenish moisture, and an anti-microbial agent to protect against infection. Use before and after work for maximum effect.

Benefits:

- Protects against dilute acids, alkalis, paints, resins, epoxies, plastics, inks, tars and petroleum solvents
- Non-greasy
- Guards against skin cracking, irritation and infection, with a pleasant perfume
- · Incorporates bactericide
- · Easily removed with soap and water
- Sprays on as a foam which collapses for maximum penetration



Graffiti Remover

Rapid penetration for fast removal of graffiti

R251 400ml

TYGRIS R251 is a powerful solvent and wetting agent based formulation making the removal of unwanted markings quick and effective, with minimal effect on the substrate. Will remove graffiti from plastics, wood, metal, glass, and most painted surfaces.

Benefits:

- Use on a wide range of surfaces including many plastics
- · Wetting agents make for effective penetration
- Methylene Chloride free
- Easy to apply
- · Rapid penetration
- Fast drying



Graffiti Remover Viscous

Thickened formula for use on vertical surfaces

R252 400ml

TYGRIS R252 – This thickened powerful graffiti remover is effective in the removal of paint graffiti, ink and felt tip, particularly on vertical surfaces or areas where the slow evaporation aids in penetration for capable erasure of unwanted marks.

Benefits:

- Thixotropic to aid in clinging to vertical surfaces
- Water washable
- · Slow drying for better penetration
- Removes paint, biro, felt tip pen
- · Easily applied
- · Non-chlorinated
- · Also effective in the removal of old gaskets



Hard Surface Foam Cleaner

Effectively dissolves grease and grime on most hard surfaces

R253 400ml

TYGRIS R253 is a solvent boosted aqueous cleaner with a foaming action used to cut through grease and grime, leaving a gleaming, smear free finish with a pleasant lemon fragrance. Its foaming properties allow it to cling to vertical surfaces and it is suitable for most hard, impervious materials.

Benefits:

- Good foam stability
- · Effectively dissolves grease and grime
- Foaming action for vertical surfaces
- · Leaves a smear free finish
- Pleasant lemon fragrance



High Wax Polish

Contains carnauba wax for a deep rich gloss

R254 400ml

TYGRIS R254 contains a blend of waxes, silicone polymer and perfumes and this is the base for this effective, high grade polish which produces a fine finish on most hard substrates. Suitable for use on polished and lacquered woods, plastics, rubber and bright metallic surfaces such as chromed finishes and stainless steel.

Benefits:

- High silicone content for ease of application
- · Contains carnauba wax for a deep rich gloss
- · Contains hard waxes for improved durability
- Cleans and shines in one application
- Pleasant odour



Ink & Gum Remover Citrus Based

Breaks down and removes stubborn ink and gum deposits

R255 400ml

TYGRIS R255 is an effective means of removing old and stubborn ink marks and gum deposits, leaving a pleasant citrus smell.

- Citrus base dissolves ink and gum
- · High softening and solubilising properties
- Breaks down old and stubborn deposits
- Pleasantly perfumed
- · Highly effective sticky label remover





Upholstery Foam Cleaner

Penetrating cleaner with foam action

R257 400ml

TYGRIS R257 is a solvent free aqueous based cleaner formulated to remove grease and grime from fabrics, including upholstery, carpets, rugs and other porous fabrics. The foaming action ensures penetration and even distribution of the spray, making the cleaning of vertical surfaces easy.

Benefits:

- Effectively removes grease and grime
- Good foam stability
- Optical whitener improves colour brightness
- Foaming action reduces wetting



Stainless Steel Cleaner

Non abrasive cleaner, leaving a protective film

R258 400ml

TYGRIS R258 maintains a sparkling appearance to stainless steel, chrome and aluminium surfaces. Its non-abrasive formulation cleans without scratching, leaving a protective film to aid in future maintenance.

Benefits:

- Non-abrasive leaves no scratches
- · Effective on stainless steel, chrome and aluminium
- Use on supermarket checkouts, window surrounds and kitchen equipment (not including food preparation surfaces)
- Removes grease
- Inert composition, acid and alkali free
- · Silicone free
- · Leaves a protective clear film
- · Lemon fragrance



Sticky Label Remover

Penetrates and dissolves adhesives

R267 400ml

TYGRIS R267 is a solvent based blend for the removal of sticky labels from most substrates including many plastics, metals, rubbers, painted surfaces and other impervious materials, leaving no residues or markings.

- · Dissolves gums and adhesives from self adhesive labels
- Suitable for most surfaces
- Leaves no residues
- High penetrating power





Clean & Polish

Wax enriched to clean and shine in one application

R246 400ml

TYGRIS R246 is a water based highly effective cleaner with a wax enriched formulation to apply a shine to sealed wood, plastic, synthetic and metallic surfaces where a clean and polished finish is desired. Being silicone based, a deep shine is imparted.

Benefits:

- Easy to apply
- Silicone based
- Wax enriched formulation
- · Multi surface application
- · Cleans and shines in one application



Shoe & Helmet Sanitiser

Anti-bacterial, anti-fungal deodorant

R247 400ml

TYGRIS R247 is a specially formulated shoe and helmet sanitiser. Fast-acting and quick drying, R247 contains both antibacterial and antifungal agents and is suitable for use with most footwear and headgear.

Benefits:

- · Fast acting, quick drying sanitiser
- Effective against the fungus which causes athletes foot
- Contains lightly scented apple fragrance
- Helps prevent cross infection and ideal for activity equipment hire e.g. bowling / biking / watersports / skating
- Also suitable for use within healthcare environments



Chewing Gum Remover

Fast and effective freezer spray

R262 400ml

TYGRIS R262 Butane based Chewing Gum Remover is a fast and mess-free way of removing gum from most surfaces. Unwanted gum is frozen into a hard lump, making it easy to chip off and remove, leaving no residue, the propellant 'flashing off' quickly.

Renefits:

- · Easily applied using the fixed extension nozzle
- Can be used on hard or soft surfaces
- High pressure discharge
- Rapid acting
- No messy residue



Label Remover HD

Fast-acting adhesive penetration and removal

R268 400ml

TYGRIS R268 is a solvent/oil-based formulation specially designed for the effective removal of sticky labels from most substrates including many plastics, metals, rubbers, painted surfaces and other impervious materials, leaving no residues or markings. Not for use on thermoplastics.

Popofite

- Rapid penetration and softening of adhesives
- Dissolves gums and adhesives from self adhesive labels
- Suitable for most surfaces
- Slow evaporation rate for an extended contact time and improved performance







Anti-Static Foaming Cleaner

Static dispersing foaming cleaner

R245 400ml

TYGRIS R245 is a foaming action cleaner designed for use around the workplace where the build up of dust is undesirable, its anti static properties dissipating static electrical charges effectively. For use on all water resistant, non porous surfaces, the foaming action aids in clinqing to vertical surfaces.

Benefits:

- · Dissolves grease and grime
- Foaming action for use on vertical surfaces
- · Minimises wetting on fabrics
- · Residual anti static effect
- For use on most surfaces including plastics
- · Streak free finish
- · Lemon fragrance



Anti-Static Cleaner

Effectively cleans leaving a residual anti-static effect and reduces dust build up

R265 400ml

TYGRIS R265 is a light duty, aqueous and alcohol based cleaner designed for use on office equipment, plastic, screens and many other surfaces where the build up of static electricity would be undesirable. Leaving a streak free finish, it leaves a residual anti static effect on both porous and impervious surfaces.

Benefits

- · Quickly removes superficial grime
- · Suitable for most surfaces
- · Residual anti static effect
- · Streak free finish on screens
- Safe on plastics



Mould & Tool Cleaner Xtra

Fast evaporating cleaner for moulds and metal components

IS25 480ml

TYGRIS IS25 effectively removes surface rust, grease and oil from injection moulds, dies and other metal components, with a fast-drying solvent which leaves no residue, for minimal down time. High powered spray effectively flushes debris from difficult to reach areas.

Benefits:

- Non-flammable CO₂ propellant
- Propellant mixes fully with product which means that the can contains a full 480ml of usable fluid
- Fast evaporating
- High powered cleaning
- Leaves no residue
- Can be used as a very effective general purpose solvent cleaner



Mould & Tool Cleaner Supa

Slow evaporating cleaner for difficult deposits

IS27 480ml

TYGRIS IS27 is used for the removal of difficult to dislodge deposits on injection moulds and metal components. Slow evaporation means that it can be used on warm moulds and can be left to work before wiping off.

Benefits:

- Slow evaporating
- · Effectively removes difficult and burnt on deposits
- Works even on warm moulds where other solvents evaporate too quickly



OneWipe™

Designed to clean tough stuff

HW101 110 wipes

TYGRIS OneWipe™ has been specifically developed for use by professionals in all trades. These large, strong and absorbent wipes contain a powerful heavy-duty hand cleaner which is proven to remove tough stuff whilst remaining safe for use on hands.

OneWipe[™] contains an aloe vera based moisturiser which conditions the skin preventing dryness and cracking. No rinsing of hands is required making the OneWipe[™] not only an excellent safe cleaner but also a convenient everyday essential.

Benefits:

OneWipe[™] will clean

- Grease & Oil
- · Silicones & Sealants
- Expanding Foam
- Paint & Epoxies
- Adhesives



Engineer's Wipes

Heavy Duty, Dual Textured Hand Wipes

HW111 111 wipes

Engineer's Wipes quickly and effectively remove contaminants such as Oil, Grease, Ink and Petrol from Hands, Tools, Machinery, and similar Interior and Exterior Surfaces whilst being equally effective for the removal of Adhesive, Bitumen, Epoxies, Joining compounds, Mastic, Paint, Polyurethanes, Polyester Fillers, Sealants and many other wet and semi-cured substances.

Benefits:

Engineer's Wipes will clean

- Grease & Oil
- Silicones & Sealants
- Expanding Foam
- · Paint & Epoxies
- Adhesives



Lubricating Maintaining

The proven formulations of TYGRIS products ensure effective lubrication in all environments including heavy

machinery applications.

Sector guide -



Automotive



Food Area



Industrial Maintenance & Operation



Metalworking & Fabrication



Plastic Moulding





Looz-n-It Penetrating Oil

Penetrates and releases corroded components on moulds and tools

IS1 400ml

TYGRIS IS1 is a premium release fluid providing a powerful penetrating action which releases and lubricates metal components which have seized through corrosion, remaining effective even under water. Giving effective penetration and lubrication without damaging paintwork, it also actively displaces moisture and does not dry off.

Benefits:

- · Fast penetration of rust and corrosion deposits
- Works effectively in wet and damp conditions
- Water repellent
- Displaces moisture
- Excellent lubrication properties
- Cleans and degreases
- · Removes moisture from ignition systems



Graphited Penetrating Oil

Graphite reinforced lubricant for tough conditions

R209 400ml

TYGRIS R209 is a graphite reinforced penetrating fluid, designed for use in semi-hostile environments, lubricating in temperatures of up to 150°C, and penetrating to free seized and corroded metallic components. The presence of micronized graphite particles provides extended lubrication intervals and is also useful for anti seize applications.

Benefits

- · Contains micronized graphite particles
- · Enhanced load bearing performance
- · Good anti-scuff properties
- · Higher temperature range than conventional oils
- · Excellent for freeing seized and corroded parts
- · Fast penetration of rust
- · Leaves a residual lubricating film



Clear Fine Oil

Clean 'light' lubricant for delicate maintenance

R211 400ml

TYGRIS R211 is a general purpose, light duty lubricant and penetrant designed to release seized components and lubricate small, delicate mechanisms.

Benefits:

- · Releases seized and rusted parts
- · Effective on small and delicate components
- Rapid penetrating action
- Use on metallic components
- Low viscosity



Clear Penetrating Oil

Clean lubricant for the release of seized and rusted components

R212 400ml

TYGRIS R212 is a clear 'low-viscosity' oil based product used to aid the removal and freeing of seized nuts and bolts, hinges, locks, tools and fittings with a fast penetrating capillary action. Leaves a clear protective film to guard against further corrosion.

Benefits:

- Low viscosity for maximum penetration
- · Easy to apply and works quickly
- · Leaves a protective film against corrosion
- · Also suitable for light lubrication duties
- · De-watering capability



De-Watering, Anti-Rust Tool Protector

Protects against corrosion for up to 2 years – indoor storage

IS3 400ml

TYGRIS IS3 is a high performance, fast drying, water displacement spray, offering both effective lubrication and medium term corrosion prevention. Use on tooling, chains, switchgear, machinery and ignition systems.

Benefits:

- Excellent water displacement chases away droplets
- Protects against rust for up to 2 years inside storage
- · Can be applied to wet surfaces
- Removes moisture from ignition systems for easier starting
- Protective film is virtually transparent and removal is not normally necessary
- The dry coating meets MOD specification 68-19 (PX-24) and NATO Code C-634



Water Displacing Anti-Rust Agent

Displaces water, penetrates, lubricates and protects

R213 400ml

TYGRIS R213 is a high performance water displacement spray which actively drives out moisture, even from hard-to-reach areas, leaving a fine lubricating film which protects against corrosion. This film enables future dismantling of equipment. Also an effective cleaner and degreaser.

- Silicone free
- Powerful water displacement properties
- · Leaves a shield against further moisture ingress
- Leaves a protective film, guarding against corrosion
- Good general lubrication for most components
- · A rapid penetrant for seized fixings



Clear Fork Lift Chain Lubricant

Anti-fling, clear chain spray with extreme pressure additives

IS75 400ml

TYGRIS IS75 is a premium-grade oil based product that gives clear lubrication to chains and other moving parts where a dark coloured lubricant would be undesirable. Its anti-fling properties make it very effective when used on moving parts, penetrating into the mechanism and depositing a film of extreme pressure additives which will withstand pressure washing.

Benefits:

- · Clear, non-staining
- Extreme pressure additives for heavy use
- Effective on fork lift chains, sprockets, pins and bushes
- Tenacious will not fling off
- · Penetrates deeply
- Withstands pressure washing
- 150°C Continuous 300°C Intermittent



Synthetic Chain Lubricant

High and low temperature

Nonfood Compounds Program Listed H1 Registration Number: 122840

IS77 400ml

TYGRIS IS77 is a highly effective clear lubricant used in the food processing industry where a tenacious non-fling product is to be used in both high and low temperature situations, actively extending chain life by excluding moisture and protecting from corrosion. Resistant to water wash off and acids, it has been specially formulated for use on slow and fast moving chains.

Benefits:

- For use on conveyor, drive and forklift chains
- · High resistance to throw off
- · Clear, non marking lubricant
- Outstanding lubrication under dynamic conditions
- · Excellent resistance to water and acids
- Working temperature from -30° to 240°C
- · Resists and prevents corrosion



Chain & Wire Lubricant

Heavy duty anti-fling lubricant

R220 400ml

TYGRIS R220 is a heavy duty, additive-reinforced lubricant which penetrates deeply into drive chains and wire ropes to give long lasting lubrication, preventing corrosion, wear and chain elongation. It gives outstanding performance under extreme load and is resistant to fling off.

Benefits:

- Use on chain blocks, drive chains, fork lift chains and wire ropes
- · Extreme pressure additives for heavy loads
- · Excellent lubrication properties
- Resistant to flinging off
- · Penetrates deeply
- Only a thin film is left on the surface for corrosion prevention
- · High resistance to wash off



Clear Polymer Chain Lubricant

Anti-fling extreme pressure water resistant lubricant

R228 400ml

TYGRIS R228 is a clear, polymer based lubricant which is used on chains and sprockets, pins and bushes where its anti-fling performance is important and where a clear invisible film is necessary for cosmetic reasons. It penetrates into the chain, depositing a film of extreme pressure additives and polymers which will withstand pressure washing.

Benefits:

- · Fortified with PTFE for improved load resistance
- · Extends chain life
- Resists and prevents corrosion
- · Clean to use
- · Penetrates deep into chain links
- 150°C Continuous 300°C Intermittent



Motorcycle Chain Wax

Anti-fling chain lubricant which doesn't attract dirt

R273 400ml

TYGRIS R273 is a high performance lubricant particularly suited for motorcycle chains. It protects against corrosion and wear and its tenacious formulation forms a water-resistant film which is easy to apply and gives long-lasting protection. The lubricant is sprayed in a semi-liquid form, thereby penetrating the chain links and subsequently thickens to a waxy consistency which is not sticky. This ensures that road dirt does not adhere, reducing wear dramatically when compared to polymer chain lubricants.

Benefits:

- Highly tenacious-resistant to flinging off
- Protects against rust and wear
- Water resistant
- · Penetrates easily, then thickens
- Resistant to adherence of dirt



Seize Release Penetrating Oil

Freezes to minus 30°C

R275 400ml

TYGRIS R275 Seize Release is an advanced formulation of Penetrating Oil with a shock freeze action which rapidly freezes seized components, causing microcracks in rust layers, and allowing rapid penetration of the lubricant.

- Tested to -31°C creating a shock effect allowing active lubricant to penetrate
- · Reduces costs through time saving
- 360° Spray system for all angle use
- · Does not contain silicones
- · Safe for use on most materials





WGRIS

Open Gear

Lubricant

Belt Dressing Anti-Slip

Reduces slippage and increases transmitted power by up to 50%

R215 400ml

TYGRIS R215 effectively boosts the performance of 'V', flat and round drive belts by reducing slippage, thereby extending belt life, reducing energy needs and the noise associated with slipping belts. Helps in the management of production costs and reduces environmental impact.

Benefits:

- Highly tacky product effectively reduces slippage
- · Suitable for all drive belts
- · Increases belt life
- Boosts transmitted power by up to 50%
- Helps in the reduction of energy costs
- · High adhesion prevents throw off
- · Resistant to oxidisation
- · Easily removed
- Temp. up to 130°C



Open Gear Lubricant

Provides a tenacious lubricant film to exposed gears and wire ropes

R216 400ml

TYGRIS R216 is a bituminous reinforced heavy duty lubricant formulated to protect and lubricate exposed gears, wire ropes and other moving parts. Exceptional penetrating and water resistance properties make it ideal for situations where exposure to weather is experienced and its tenacity resists throwing off during use.

Benefits:

- · Highly resistant to throw off
- Water resistant for use in adverse weather conditions
- · Good penetrating qualities
- Excellent lubricating power
- High pressure foaming discharge imparts excellent penetrative power
- · Protects against corrosion, wear and salt
- · Resistant to embrittlement over long usage





Drive and Bearing Lubricant

Extreme pressure lubrication for drive chains and bearings

R229 400ml

TYGRIS R229 is an effective lubricant for the lubrication of chains, bearings and wire ropes. Containing extreme pressure and anti-fling additives, this enhances chain and rope life whilst having minimal effect on rubber O-rings and components, and can be used at a wide range of temperatures.

Benefits:

- Anti-fling properties for moving chains
- Extreme pressure additives for long arduous service
- Not aggressive to rubber parts
- Wide temperature range
- Use on drive chains, wire ropes and bearings
- 100°C Continuous 150°C Intermittent



Super Lube Extreme Pressure

4 in 1 PTFE reinforced de-watering anti-rust penetrating and protecting lubricant

R232 400ml

TYGRIS R232 is a PTFE reinforced lubricant with excellent penetrating properties. De-waters, lubricates, releases and protects.

- PTFE reinforced for excellent anti-friction capabilities
- Extreme pressure additives
- PTFE is grafted onto wax particles for better substrate adhesion
- 60°C Continuous 80°C Intermittent
- · De-watering additives
- Effective penetration and release
- · Corrosion inhibitors





Aluminium Anti-Seize

High temperature anti-seize protection up to 800°C

R233 400ml

TYGRIS R233 is a high temperature multi purpose blend of heat stable lubricant and anti-seize compound used in a wide range of automotive, industrial, marine and construction applications, helping to eliminate seizure, pitting and rusting of components exposed to heat. Use on threaded components, flanges, chains and locks to facilitate in future dismantling.

Benefits:

- Prevention of seizure
- Assists in easy dismantling of threaded parts
- · Effective lubrication at ambient temperatures
- High temperature resistance to melting
- Use also on flanges, chains and locks
- · Facilitates easy re-use of dismantled components
- Temp. range: -30°C to +275°C



Copper A-S Advanced

High temperature anti-seize protection up to 1100°C

R234 400ml

TYGRIS R234 is a high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. Resistance to water and acids is high and it will not burn off under extreme stress. For use on threaded components, pins, valve stems in a range of materials including austenitic stainless steel. Used on brake callipers and the back of brake pads it will help eliminate brake squeal.

Benefits:

- Effective up to 1100°C
- · Water and acid resistant
- Use on a wide range of metals
- Prevents seizure of threaded parts
- · Will not burn or wash off
- · Eliminates brake squeal
- Assists in assembly and disassembly of components



Moly Dry Film Lubricant

High load – high temperature dry lubricant

R218 400ml

TYGRIS R218 is a molybdenum disulphide based lubricant for use where conventional wet oils would be undesirable. Particularly suitable for the assembly and running-in of gears, bearings, spindles and valves, it is effective for use where high temperatures occur, drying to a tough, matt black high slip coating.

Benefits:

- Dry Lubricant does not attract dirt
- Durable coating
- · Outstanding adhesion
- Extended service life
- Withstands high loads
- Working temperature to at least 350°C
- · Water and chemical resistant
- Anti static properties



PTFE Dry Film Lubricant

Dry PTFE based lubricant for quick and clean assembly and dismantling

R237 400ml

TYGRIS R237 is an effective dry film non-staining lubricant for use where wet oils would be undesirable. For use in the assembly of metal components and the lubrication of machine slides, cams and cutting shears in engineering applications.

Benefits

- PTFE dry film for very low friction (PTFE has the lowest friction of any known solid)
- Durable coating
- Non-toxic completely inert
- Anti-static
- High working temperature up to 275°C
- Withstands low temperatures
- Water and chemical resistant
- Rapid drying
- · Non-greasy dry film does not attract dirt



Silicone Lubricant

Non staining lubricant with high temperature stability

R217 400ml

TYGRIS R217 provides clean, low odour, non-staining lubrication for many applications, especially plastic parts and seals. Non-toxic in character, making it suitable where incidental food contact may occur.

Benefits:

- Excellent lubricating properties
- · Non-staining, low odour
- Effective on plastic, metal, wood, vinyl, rubber and other surfaces
- Non-toxic for use where incidental food contact may occur
- · Used for mould release in the plastics industry
- An effective surface polish
- Use on seals, slides, bearings, textile equipment etc.
- High temperature stability up to 200°C
- · Water repellent



White Grease with PTFE

Clean water resistant grease reinforced with PTFE

R223 400ml

TYGRIS R223 is a premium quality anhydrous calcium based grease for use in applications requiring good water resistance. For use in anti-friction and plain bearing pumping equipment and in the lubrication of linkages, door latches, hinges, gears, springs, bearings, rubber components, 'O' rings, striker plates and sliding shackles.

- · High water resistance for marine use
- · Prevents corrosion in humid conditions
- Prevention of seizure
- · Good mechanical stability
- Wide temperature Range from -20°C to 110°C
- Reinforced with PTFE for improved slip properties





Ceramic Release Spray

Release spray for use on welding torches and extrusion dies

IS35 400ml

TYGRIS IS35 is a ceramic/boron nitride spray for use as a dry film protective coating on MIG welding torches, jigs, fittings and cables etc to prevent the adhesion of welding spatter. Also used as an excellent lubricant on moulds and dies used in aluminium extrusion processes.

Benefits:

- Protects welding torches, jigs and fixtures from welding spatter reducing downtime costs
- Physical barrier protects surfaces from heat
- Extends shroud service life
- Safe for use on metal components, cables and sensors
- Easy to apply with excellent adhesion
- Silicone free so compatible with post finishing processes
- · Application only required once or twice a shift



Food Safe Lubricant

Penetrating lubricant for use in food processing areas

InS Registration Number: 1797125

R219 400ml

TYGRIS R219 is a vegetable oil based lubricant, H1approved for use in and around food processing areas where incidental food contact may occur. It is odourless, colourless, contains anti-throw additives and is formulated to penetrate cable cores.

Benefits

- InS: H1 registered for use in food environments
- No animal derivatives
- · Silicone free
- · Odourless, colourless and non-staining
- Anti-throw properties for moving chains
- Penetrates cable cores
- · Use on chains, slides, gears and linkages etc.
- Good temperature range
- 180°C Continuous 200°C Intermittent



Cutting and Tapping Fluid

Contains extreme pressure additives to reduce tool wear and improve machined finish

R214 400ml

TYGRIS R214 is a ready to use cutting and tapping fluid specially formulated to improve tool performance and extend tool life. It contains additives to prevent pitting, galling and metal seizure and is suitable for use on hard to work metals including stainless steel, titanium, aluminium and tool steel.

Benefits:

- For cutting, tapping, reaming and turning
- Extreme pressure additives for difficult materials
- High pressure, frothy discharge to aid penetration
- Prolongs tool life and improves machined finish
- Reduces heat build up
- Suitable for use on all metals
- · Incorporates corrosion inhibitors



Metal Working Spray

Penetrating cutting enhancer and cooling agent for hard metals

R208 400ml

TYGRIS R208 Metal Working Spray has been developed specifically to meet the cutting lubrication demands of harder metals such as stainless steel. Its enhanced extreme pressure additives and non-solvent, high mineral oil contents make R208 a consistently high performing lubricant which cools and penetrates to enable a clean cutting action and increase tool life.

Benefits:

- Proven performance on stainless steel
- · Fast flowing and penetrating formula
- Solvent free
- Enhanced extreme pressure additives
- · Developed for hard materials
- · Suitable for cutting, tapping, drilling and reaming
- Reduces heat build up
- Prolongs tool life and improves machined finish



Clear Grease

Non staining, extreme pressure grease for high load applications

R226 400ml

TYGRIS R226 is used on chains and moving metal parts. This high performance grease penetrates rapidly before thickening to a tenacious grease which is highly resistant to throw off. The addition of extreme-pressure additives makes it particularly effective under heavy loads.

Benefits:

- · Clear, non-staining
- Penetrates rapidly and thickens
- Highly resistant to throw-off
- · Extreme-pressure additives for high loadings
- Use on chains and other moving parts



Clear Silicone Grease

Clear, moisture resistant, silicone based grease

R230 400ml

TYGRIS R230 is waterproof silicone based grease which is very effective for the insulation of electrical components and parts as well as being an excellent sealant against moisture. Ideal for use on rubber seals and many other exterior applications.

- Effective moisture resistance
- Preserves rubber components
- Clear formulation
- Good electrical insulating properties
- · Can be used for parts assembly and disassembly
- 80°C Continuous 150°C Intermittent



White Grease

Water resistant white grease

Nonfood Compounds Program Listed H1 Registration Number: 139270

F402 400ml

TYGRIS F402 is a highly effective white spray grease containing anti-wear additives for use in the lubrication of roller and needle bearings and chains.

Benefits:

- H1 registered for use in food environments
- Contains anti-wear additives for long component life
- Water resistant suitable where frequent washing down of equipment is required
- · Corrosion resistant
- Effective to high temperatures
- Temp. range: -20°C to +200°C
- 360° valve for inverted use



Multi-Lube

Multi-purpose lubricant

Nonfood Compounds Program Listed H1 Registration Number: 139271

F404 400ml

TYGRIS F404 is a general purpose food grade lubricant for use in and around food processing areas, for the lubrication of cables, chains, castors, hinges, bearings and pins.

Benefits:

- H1 registered for use in food processing environments
- Effective over a wide temperature range
- Good water displacement
- Good penetration properties
- · Effective corrosion resistance
- Temp. range: -20°C to +200°C
- 360° valve for inverted use



ProPaste

High performance, multi-purpose lubricant

Nonfood Compounds Program Listed H1 Registration Number: 154797

F405 400ml

PROTEAN ProPaste is a NSF: H1 registered sprayformulated tenacious food grade lubricant. Engineered as an anti-seize paste, PROTEAN ProPaste is ideal for the assembly and lubrication of bushes, slides, threads and small open gears and also suitable as a drilling, cutting and tapping lubricant in areas where in-situ repair and maintenance is required.

Benefits

- H1 registered for use in food environments
- · Highly tenacious lubricant resists water wash off
- Ideal for use on stainless steel fasteners
- · 360 valve for inverted use



Chain Spray

Anti-fling chain spray

Nonfood Compounds Program Listed H1 Registration Number: 139272

F408 400ml

TYGRIS F408 is a food grade chain spray which is a highly tenacious, anti-fling lubricant designed to keep chain and drive systems operating smoothly. Being non-toxic and water resistant it is ideal when used on food conveyor systems requiring frequent wash down.

Benefits:

- H1 registered for use in food environments
- Non-toxio
- Water resistant withstands washing
- · Anti-fling for fast moving components
- · Highly tenacious will not drip off
- Anti-corrosion additives
- · Withstands high temperatures
- Temp. range: -20°C to +200°C
- 360° valve for inverted use



PTFE Dry Film Lubricant

PTFE dry film lube

Nonfood Compounds Program Listed H1 Registration Number: 139294

F410 400ml

TYGRIS F410 is a PTFE based dry film lubricant for use in food processing environments, formulated for use where conventional oils and greases are undesirable due to their dirt attracting nature.

Benefits

- H1 registered for use in food environments
- PTFE- based lubricant for excellent anti-stick properties
- Use to lubricate links, pins and slides
- Effective release agent
- Non-toxic film
- Withstands high temperature
- Temp. range: -20°C to +270°C
- 360° valve for inverted use



Penetrating Oil

Penetrating and release fluid

Nonfood Compounds Program Listed H1 Registration Number: 139298

F412 400ml

TYGRIS F412 is a penetrating and release fluid with anti-corrosion properties which actively penetrates seized components. A residual lubricating film adheres to the released part, facilitating re-assembly and helping prevent further corrosion. Effective over a wide temperature range, the all angle valve allows use in an inverted position.

- H1 registered for use in food environments
- Powerful penetration through rust, scale and grime
- · Leaves a corrosion resistant coating
- Acts over a wide temperature range
- Temp. range: -20°C to +250°C
- 360° valve for inverted use





WD Anti-Rust Agent

Moisture displacement spray

Nonfood Compounds Program Listed H1 Registration Number: 139267

F416 400ml

TYGRIS F416 is a PTFE based aerosol effective for use in displacing moisture and water based fluids from most surfaces, leaving a residual film of lubricant. Used on sliding surfaces, in bearings and for other light applications in food processing environments.

Benefits:

- H1 registered for use in food environments
- · PTFE based for effective moisture displacement
- Use for light lubrication
- · Leaves a film of lubricant
- Temp. range: -20°C to +250°C
- 360° valve for inverted use



Silicone Release

Silicone release lubricant

Nonfood Compounds Program Listed H1 Registration Number: 139266

F418 400ml

TYGRIS F418 is an effective lubricant and release agent for the food industry, used to protect and lubricate a wide range of parts and equipment and for the release of injection moulded parts when traditional oils are not suitable.

Benefits:

- H1 registered for use in food environments
- · Silicone based an alternative to traditional oils
- Colourless and odourless
- Non-staining and non-tainting
- Wide temperature range
- · Excellent release properties
- Temp. range: -20°C to +200°C



Seize Release+

High performance, fast acting dismantling lubricant

Nonfood Compounds Program Listed H1 Registration Number: 154795

F428 400ml

PROTEAN Seize Release+ is a NSF: H1 registered spray-formulated, fast acting penetrating and dismantling food grade lubricant. Engineered to 'shock' components through rapid freezing, PROTEAN Seize Release+ quickly penetrates seized and rusted parts, enabling optimum 'release' and easy dismantling.

Benefits

- H1 registered for use in food environments
- Fast acting 'Freeze & Release' action for easy dismantling of seized and rusted parts
- Enables rapid and efficient wicking of the lubricant for deep penetration
- Suitable for use on all metals and most common plastics and rubbers
- Released parts remain lubricated and protected from corrosion
- · 360°C value for inverted use



3H1 Grease (Spray)

High performance direct contact grease

Nonfood Compounds Program Listed 3H & H1 Registration Number: 152452

F430 400ml

PROTEAN 3H1 Grease (Spray) is a non-toxic, wide temperature, multi-purpose grease offering enhanced anti-wear performance for prolonged component life. PROTEAN 3H1 Grease (Spray) prevents food products from adhering to surfaces during processing and is suitable for most applications where direct food contact is inevitable.

Benefits:

- Suitable for use as a direct food contact release agent and multi-purpose lubricant
- Exhibits superior EP performance with a 4-ball weld load of 400kg
- Excellent lubrication performance and enhanced oxidative stability for both extending lubrication intervals and reducing lubricant usage
- Ideal for bearings, blades, guides, seals and other sliding surfaces
- Temp. range: -30°C to +120°C



3H1 Fluid (Spray)

High performance direct contact fluid

Nonfood Compounds Program Listed 3H & H1 Registration Number: 152596

F435 400ml

PROTEAN 3H1 Fluid (Spray) is a high performance, multi-purpose oil, engineered for use within food production environments where direct food contact is unavoidable. PROTEAN 3H1 Fluid (Spray) prevents food products from adhering to surfaces during processing and also acts as a protective anti-rust film on metal surfaces, meat hooks and knives.

- Suitable for use as a direct food contact release agent and multi-purpose lubricant
- · Non-tainting, clear and odourless
- Ideal for use on loaf pans, baking trays, chopping boards, boning benches and other hard surfaces that come into contact with food products
- Good sealing properties protect against unwanted corrosive contaminants
- Temp. range: -10°C to +120°C





Non-Silicone Mould Release Agent

Effective non-silicone mould release up to 200°C

R225 400ml

TYGRIS R225 is a non-silicone release agent for use in the Plastic Moulding industry, where further finishing processes are to be carried out. With a non-chlorinated, solvent-free vegetable oil base, it is stable up to a temperature of 200°C. Conventional detergents easily remove any residue of this benign, non-toxic agent, allowing for further product finishing.

Benefits:

- Non-silicone content to allow for overpainting, lacquering, overprinting, gluing or welding
- Excellent surface slip
- Effective where a high gloss finish is desirable
- Easily removed by conventional detergents



Mould Release Non-Silicone

Effective silicone free release for up to 220°C

IS13 400ml

TYGRIS IS13 is an excellent alternative to silicone spray for use in the Plastic Moulding industry. It is a quick drying solvent and oil blend with a vegetable oil base, stable up to 220°C. It is non-chlorinated and is easily removed by ordinary washing, facilitating further product finishing.

Benefits

- Non-silicone content to allow for overpainting, lacquering, overprinting, gluing or welding
- Excellent release and flow properties
- · Virtually odourless mild solvent which "flashes off"
- · Effective where a high gloss finish is desirable
- Quick drying
- Easily cleaned off with conventional detergents



Mould Release Light

Light duty release agent for delicate moulds

IS9 400ml

TYGRIS IS9 Mould Release is ideal for the release of delicate plastic mouldings. This is particularly useful where marking of the plastic might otherwise occur. Used to give fine and lasting lubrication in a wide range of industrial applications, it is stable up to 300°C.

Benefits:

- 8% silicone for delicate and small mouldings
- · No other additives
- Good flow properties
- · Colourless and non-marking
- · Safe and odourless
- Gives lasting lubrication
- Heat stable up to 300°C



Mould Release Medium

Medium duty release agent with added PTFE

IS5 400ml

TYGRIS IS5 contains a special blend of 10% silicone and PTFE, resulting in a very effective, proven mould release agent for the Plastic Injection Moulding Industry. Being colourless, it is non-staining and is heat stable up to 300°C.

Benefits:

- 10% silicone
- Added PTFE for an effective release agent increasing the number of releases
- No other additives
- Maximum surface slip
- · Colourless and non-marking
- Virtually odourless
- Stable up to 300°C



Mould Release Heavy

Heavy duty release agent

IS10 400ml

TYGRIS IS10 is a heavy duty mould release agent with a 15% silicone content used for the release of more difficult plastic mouldings. Safe, colourless and non-staining it is useful as a lubricant around the workplace, and is temperature stable up to 300°C.

Benefits:

- 15% silicone content for larger mouldings
- · Excellent release properties
- · Very high surface slip
- Colourless and non-marking
- Odourless and inoffensive
- Effective as a general lubricant
- Heat stable up to 300°C



Synthetic Ejector Pin Lubricant

High temperature ejector pin lubricant

Nonfood Compounds Program Listed H1 Registration Number: 122839

IS45 400ml

TYGRIS IS45 is a high temperature, food area safe, synthetic product suitable for the lubrication of ejector pins, pillars and bushes on plastic injection moulding machines. Highly tenacious lubricant with an operating temperature of up to 240°C which will reduce contamination to mouldings, helping to prevent seizure and to protect against corrosion.

- Highly tenacious resistant to 'creeping' on ejectors
- Provides long lasting lubrication
- Reduced mould contamination
- High surface slip
- · Water resistant, fully synthetic
- · All angle valve can be used inverted



One Brand... Infinite Appeal...





TYGRIS SOS Direct

Trying new products is often a daunting proposition, especially if you have to buy products without trying them first.

So confident are we in our products, TYGRIS SOS-Direct offers samples at no cost or obligation, providing peace of mind for distributors and consumers alike.

Try TYGRIS with confidence knowing that you can try our products FREE of charge. If the sample doesn't do what you need it to do, we'll send you an alternative sample to try, direct to your door! We'll even include a treat as a thank you for trying TYGRIS.

There is a better way... try SOS-Direct today!



TYGRIS Aware

Empowering valued distributors to effectively market TYGRIS Cleaning, Lubricating and Protecting consumables remains our core mission, and has done so for many years.

TYGRIS prides itself on the expertise of our teams and the collaborative information sharing amongst distributors and consumers alike.

TYGRIS Aware allows our support teams to deliver custom on-site TYGRIS Awareness sessions in order for distributors to effectively market and sell our comprehensive range of TYGRIS products.

Contact us today and become Aware!



TYGRIS 4Li

Having confidence in products is paramount for all engineers, regardless of application, sector or working environment.

> So confident are we in our products, we offer the **TYGRIS 4Life** guarantee, providing peace of mind for distributors and consumers alike.

Buy TYGRIS with confidence knowing that our products have been rigorously tested, tried and proven; conform to current legislation; and will work for the purpose intended. Look out for the TYGRIS 4Life guarantee logo printed on our products - the stamp of quality assurance to ensure 100% satisfaction.

Believe in our products like we do... 4Life!





Meeting the everyday Cleaning, Lubricating and Protecting needs of our valued

consumers remains core to our continued business growth and increasing global

TYGRIS prides itself on the relationships we have fostered with distributors and consumers alike.

TYGRIS Connect allows our on-site assessment teams to better understand the real-time challenges that consumers face in the workplace; whether it's to identify the right TYGRIS products to optimise efficiencies, yield labour savings or just to simply make life that little bit easier.

Contact us today and make that connection!







Crack Detector Cleaner No. 1

Solvent Cleaner
Part 1 of the TYGRIS 3 part
non-destructive testing system

IS91 400ml

TYGRIS IS91 – Part 1 is an effective slow-drying solvent cleaner used as part of the 3 part non-destructive crack detection system. It prepares the surface to be tested by cleaning and removing surface films.

Benefits:

- Slow drying for effective cleaning
- · Suitable for use on all metals
- Excellent solubilisation of oil, grease and other organic matter
- · Residue free



Crack Detector Red Dye No. 2

Dye Penetrant
Part 2 of the TYGRIS 3 part
non-destructive testing system

IS92 400ml

TYGRIS IS92 – Part 2 is a highly penetrative bright red dye solution designed for rapid absorption into surface faults and imperfections, used as the second part of the 3 part non-destructive crack detection system for metallic surfaces.

Benefits:

- Exposes defects on metalwork, castings, forgings, pressure vessels etc
- Bright red with excellent colour coverage
- · Good wetting properties
- · Reliable exposure of open flaws



Crack Detector Developer No. 3

White Powder Developer Part 3 of the TYGRIS 3 part non-destructive testing system

IS93 400ml

TYGRIS IS93 – Part 3 is a developer used to enhance and clearly show any defects in metal castings and forgings etc, drying to a white, opaque powdery coating and providing an excellent contrasting background previously treated with Dye Penetrant. Used as the third and final part in the non-destructive testing system.

Benefits:

- · Provides maximum sensitivity and defect exposure
- Excellent colour contrast
- · Very fast drying
- Outstanding wetting properties



Leak Detector

Non-flammable gas leak detector

R236 300ml

TYGRIS R236 is an inoffensive, non-corrosive foam used in the inspection of pipework to prevent leaks passing unnoticed with potentially dangerous effects. It will detect any leaks instantly and is harmless to most materials as well as being safe to use with most gases.

Benefits

- · Non-flammable water based
- Completely inert
- · Will detect the smallest leaks
- Will not form combustible mixture with other gases
- · Can be used with oxy-acetylene and LPG gases
- Non-corrosive
- Nitrogen propellant
- Easily removed completely water soluble
- Temp. range: -20°C to +200°C
- Conforms to BS EN ISO 14921 EU Regulations for use in Department of Transport testing stations



Heavy Duty Adhesive Non-Chlorinated

Non-chlorinated 'repositionable' strong adhesive

R260 400ml

TYGRIS R260 is an easy to use, repositionable adhesive for bonding most surfaces, including textile, foam, rubber, plastic, foil, cardboard and paper. Good for fixing down carpets, underlay and floor tiles. In a non-chlorinated form for maximum safety.

Benefits:

- Strong, repositionable adhesion
- Fast drying
- · Bonds most surfaces
- · Variable discharge fan nozzle
- · High strength bond



Heavy Duty Adhesive

Non-chlorinated High Strength adhesive

R210 500ml

TYGRIS R210 is an easy to use adhesive for bonding most surfaces, including textile, foam, rubber, plastic, foil, cardboard and paper. Good for fixing down carpets, underlay and floor tiles. In a non-chlorinated form for maximum safety.

- Fast drving
- Bonds most surfaces
- Variable discharge fan nozzle
- · High strength bond
- 22 Litre canister also available (TBR210)





Circuit Freezer Spray (Low GWP)

Non-flammable rapid cooling agent

R240 400ml

TYGRIS R240 is a rapid cooling agent used in a number of applications where lowering the temperature quickly is beneficial, including the detection of electronic equipment faults, working on small bore water pipes, and shrink fitting of close-tolerance metal parts. A non-flammable, inert, liquefied gas.

Benefits:

- F-GASES II (EC) REGULATION 517/2014 Compliant Product. Low GWP (Global Warming Potential) with NO ozone depletion potential
- · Rapidly cools components to freezing point
- Detects faults in electronic circuits by reducing the temperature
- Use to shrink fit metal parts
- · Quickly freezes small bore pipes for safe working
- Can be used to freeze gum toffee candle wax and other soft deposits



Rapid De-Icer Water Free

Active down to -15°C

R227 400ml

TYGRIS R227 is a concentrated solvent-based rapid de-icer for windows, locks, hinges and mechanisms in extreme conditions. Being water free, re-freezing will be prevented down to -15°C. The CO₂ propellant means application is effective at below freezing temperatures.

Benefits:

- · Water free, alcohol based
- · For de-icing windscreens, door locks, hinges etc.
- Remains active to -15°C, preventing re-freezing
- Inclusion of ammonia provides good detergent properties
- High pressure discharge for coldest conditions
- CO₂ propellant
- Safe on paintwork and windscreen wiper rubbers







Weld Spatter Release Spray (Solvent Based)

Non-silicone weld spatter release spray

R221 400ml

TYGRIS R221 is a special non-silicone formulation ideal for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools and enables free gas flow in inert gas welding.

Benefits:

- Non-silicone can be used with products that require finishing
- Rapid drying
- · Prevents adhesion spatter easily removed
- Colourless non-staining
- · Does not gum up when subject to heat
- Non-flammable for maximum safety



Weld Spatter Release Spray (Water Based)

Non-silicone, non-flammable weld spatter release spray

R222 400ml

TYGRIS R222 is a water based solvent-free formulation for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools. Its water based properties offer an environmentally friendly alternative to solvent based varieties.

- Prevents spatter adhesion
- Non-silicone can be used with products that require finishing
- · Excellent non-stick finish
- Non-flammable
- Water rinseable
- · Dichloromethane free

CALLING TYGRIS SOS...



Trying out new products can often be a daunting proposition, especially if you have to buy products without trying them first.

So confident are we in our products, our Sample Order Service, more commonly known as **TYGRIS SOS**, provides samples at no cost or obligation, providing peace of mind to both TYGRIS distributors and end-users alike.

Try TYGRIS with confidence knowing that you can try our products FREE of charge. If the sample doesn't quite do what you need it do, we'll send you alternative sample to try, direct to your door! We'll even include a TYGRIS treat as a thank you for trying TYGRIS.

ORDER YOURS TODAY...

by contacting your preferred TYGRIS distributor or ordering online at www.tygrisindustrial.com







Protecting

Finishing

With over 40 years of experience, TYGRIS Protecting and Finishing products offer lasting results for all your interior and exterior needs.

Sector guide -



Construction, Site & Warehousing



Industrial Maintenance & Operation







Battery Terminal Protector

Protective coating containing pH indicator to detect leaks

R204 400ml

TYGRIS R204 is an easily applied fine film spray which protects battery terminals by sealing them from air and moisture, prolonging battery life and increasing its efficiency. Corrosive deposits are prevented from building up and the coating contains a pH indicator to detect the incidence of leaks.

Ronofite

- Easily applied spray
- Protects battery terminals from deterioration
- Prolongs battery life
- Increases starting efficiency
- pH indicator dye detects battery acid leakage and turns from orange to red
- Dries to a thick non-slumping grease
- Water repellent



Clear Acrylic Lacquer

Durable coating for sealing and protecting

R242 400ml

TYGRIS R242 is a fast drying coating used to protect against mild acids, alkalis and general weathering. For sealing and protecting electronics, metal, wood, and paper documents, leaving a smooth, transparent, scratch resistant film with good durability and toughness.

Benefits:

- Fast drying
- · Excellent resistance to weathering and sunlight
- · High resistance to mild acids and alkalis
- · Touch and scratch resistant
- Good resistance to water and salt spray
- Easy to apply
- Max. Temp. 50°C



Clear Mould Protector

Clear film protection for moulds and tools

IS60 400ml

TYGRIS IS60 is a clear Metal Protector, used for the protection of moulds and tools, leaving a clear, invisible film which is easy to remove or mould off. Used extensively in the plastic moulding industry it is non-staining and an efficient de-watering agent.

Benefits:

- · Removes water from the surface of all metals
- Clear, invisible film
- · Non-staining
- · Thin coating easily removed or moulded off
- Up to 2 years inside storage protection



Green Mould Protector

Thin film protection for moulds and tools

IS70 400ml

TYGRIS IS70 is an effective moisture displacement, formulated to provide an ultra-thin green film for protection from corrosion of moulds and tooling whilst in store. Used extensively in the plastic moulding industry. Easy to clean or mould off.

Benefits:

- · Suitable for use on all metals
- De-watering capability
- · Protects from oxidisation and rusting
- Ultra-fine film does not interfere with precision-fit parts or with gauging and measurement
- Green colour to show treated parts
- Resists creeping into ejector pins
- · Moulds off quickly



Green Moisture Guard

Protects against moisture for moulds and metal tooling

R266 400ml

TYGRIS R266 is an effective moisture repellent, formulated to provide an ultra-thin green film for protection from corrosion of moulds and tooling whilst in store.

Benefits:

- De-watering capability
- Protects from oxidisation and rusting
- Ultra-fine film (3-5 microns) does not interfere with precision-fit parts or with gauging and measurement
- Green colour to show treated parts
- Resists creeping into ejector pins
- Moulds off quickly



AtmoShield+

High performance corrosion inhibitive wax film

Nonfood Compounds Program Listed H1 Registration Number: 154794

F426 400ml

AtmoShield+ is a NSF: H1 registered spray-formulated heavy duty wax film, enriched with corrosion inhibitors and suitable for use within Food & Beverage environments. Providing long term protection against corrosion on metal components and equipment, and resistant to both water wash-off and cleaning, PROTEAN AtmoShield+ is ideal for use on machined surfaces and assemblies that are subjected to long periods of storage or shipping conditions.

- Corrosion inhibitors long-term metal protection
- Clean white film for improved coverage visibility
- Tenacious heavy duty wax film resistant to wash wash-off and cleaning
- 360° valve for inverted use



Bright Zinc Galve Spray

Quick drying zinc protective coating

R224 400ml

TYGRIS R224 is a bright zinc and aluminium powder based spray used for the cosmetic finishing and protection of previously galvanised surfaces where the component has been cut or welded, thereby exposing metal to the air. Zinc is a sacrificial metal and will prevent oxidisation and corrosion. Resins in the coating cause it to bond firmly to the substrate.

Benefits:

- Zinc content assists in corrosion prevention
- · Resistant to salt spray and weathering
- Excellent heat resistance
- Aluminium powder gives a brighter finish to help blend with existing coatings
- · Can be used on previously coated surfaces
- High purity powders
- Excellent adhesion
- Quick drying
- 150°C Continuous 400°C Intermittent



Zinc Galvanising Spray Heavy Duty

Durable zinc protector and primer

R239 400ml

TYGRIS R239 is a high quality zinc spray providing active metal protection against corrosion and an excellent primer coat. The sacrificial properties of zinc contribute to an effective defence against oxidisation should the coating become damaged. Zinc Galvanising Spray can be used both on bare metal and previously galvanised surfaces, and is suitable for spraying onto acrylic or cellulose paints (not alkyd). It may be over-coated with acrylic, alkyd, p/u alkyd and epoxy.

Benefits:

- High zinc content for maximum corrosion prevention, including salt spray
- · Zinc powder in the product is of high purity
- · Can be used on previously coated surfaces
- · Can be over-coated



Bright Zinc Cold Galvanise


Bright zinc aluminium protective coating

TC101 400ml

TYGRIS TC101 Bright Zinc Cold Galvanise is a fast drying anti-corrosive coating, suitable for use on both ferrous and non-ferrous metals. TC101 can be used as a primer and topcoat and ideal for repairs to cut or damaged galvanised surfaces.

Benefits:

- Long-lasting corrosion prevention
- All-in-one primer and topcoat
- Fast drying
- touch dry in 10mins @ 20°C
- hard dry in 30mins @ 20°C
- Provides a bright aluminium finish that weathers naturally over time
- Coverage approx. 9m² per litre (applied @ 50 microns)



GalvShield+

Cold Galvanising Zinc-Rich Protection


TC204 400ml TC208 800ml TC219 1.9Ltr

TYGRIS GalvShield+ is a single component, zinc-rich cold galvanizing protective coating suitable for use as a self-finish, or as a primer in a duplex system. Designed to protect all ferrous metals and prevent 'rust creep', TYGRIS GalvShield+ can be brush or spray applied and is ideal for use as a touch-up to damaged galvanised surfaces, or where hot dip galvanising is either impractical or cost-prohibitive.

- Can be used as both a primer / self-finish and provides an effective key for overcoating
- · Dried film contains in excess of 90% zinc by weight
- · Provides excellent adhesion flexibility durability and resistance to mild abrasion
- Prevents rust creep from exposed areas of substrate thus also preventing the lifting of an applied paint film
- Fast drying can be applied as a shop or field coat
- Suitable for use on structural steel curtain walls iron railings roof decks transmission towers culverts ducts
- Ideal for a variety of marine/offshore applications
- Provides up to 1000 hours resistance to Hot Salt Spray when tested to ASTM B117 standard



TYGRIST VariSpray Paint



TYGRIS VariSpray paint is a professional formulation paint developed for the effective finishing of treated and untreated materials such as metal, aluminium, glass, stone and various types of plastics whilst providing beneficial features for the user. The VariSpray corrosion preventative formulation stands it apart from typical paints and provides the protection required to ensure a long lasting finish.

Adjustable nozzle for varied width and angle of spray

Colour coded collar for ease of identification – doesn't come off like caps do!

Corrosion preventative formulation

High adhesion, fast drying formulation

High coverage and filling properties

Scratch free and shock proof finish

UV resistant, non fading and long lasting results



Turn the page for more information on our TYGRIS range of stock colours and best-selling TYGRIS VariSpray Custom Colour Service



VariSpray Acrylic-Based Primers and Finishing Paints

Premium quality high opacity paint

TYGRIS Acrylic-based top-coat paints and primers can be used for a professional finish on most substrates with exceptional ease of use, resulting in a high quality appearance.

Benefits

- Acrylic formulation for greater flexibility
- · Gives excellent adhesion
- Compatible with most materials
- · Can be applied over previously painted surfaces
- High opacity
- Lead Free
- Excellent UV stability

P300	Matt Black Paint	RAL9005	400ml
P301	Satin Black Paint	RAL9005	400ml
P302	Gloss Black Paint	RAL9005	400ml
P303	Grey Primer		400ml
P304	White Primer		400ml
P305	Red Oxide Primer		400ml
P306	Gloss White Paint	RAL9003	400ml
P307	Bright Silver Paint	RAL9006	400ml
P308	Black Primer		400ml
P309	Self-Etching Primer		400ml
P310	Gloss Blue Paint	RAL5010	400ml
P311	Gloss Green Paint	RAL6001	400ml
P312	Gloss Red Paint	RAL3000	400ml
P313	Gloss Yellow Paint	RAL1007	400ml
P314	Gloss Orange Paint	RAL2004	400ml
P315	Gloss Dark Green Paint	RAL6005	400ml



High Temperature Paint

High quality paint with safe working temperature up to 800°C

P330 Black VHT 400ml **P334 Aluminium VHT** 400ml

TYGRIS Very High Temperature Paint has a safe working temperature of 800°C and when applied as directed, requires no primer. This high quality paint is suitable for machinery, industrial and automotive components and can also be used on domestic products.

Benefits:

- Very high temperature resistance
- No primer required
- Touch dry within 30 minutes



Self-Etching Primer

Premium one-step etch primer

P309 400ml

TYGRIS P309 is an acrylic-based high performance self-etching primer and designed to prepare clean bare metal surfaces, aluminium and fibreglass for a topcoat finish. Specially formulated with inhibitors for effective corrosion prevention, P309 provides optimum adhesion to bare substrates and is ideal for use with the TYGRIS VariSpray range of top coat paints.

- Acrylic formulation for greater flexibility
- Easy to use dual-action etch / primer
- · Provides optimum adhesion
- Compatible with most substrates
- High opacity
- Lead Free
- · Excellent UV stability
- TYGRIS Variable Nozzle







Stripeline Marking Paint

Durable fast drying semi-permanent paint for hard surfaces

LMBE	Blue	750ml
LMBK	Black	750ml
LMGN	Green	750ml
LMOE	Orange	750ml
LMRD	Red	750ml
LMW	White	750ml
LMY	Yellow	750ml

TYGRIS Line Marker is a solvent based paint used for applying semi-permanent markings to most hard surfaces, inside or outside. Used inverted with a hand held or wheeled applicator, this paint is rapid drying and has good resistance to abrasion and chemicals. Available in 7 colours for safety and legal purposes.

Benefits:

- · Easy to apply by hand or applicator
- · Fast drying
- · Lead and xylene free
- · High opacity
- Anti-clogging nozzle
- UV-stable
- · Excellent abrasion and chemical resistance
- Compatible with most applicators
- 7 colours available

Stripeline Paint Applicators

HHA Hand Held Applicator

Use this handy applicator to do spot marking or short line marking work with TYGRIS Stripeline paint. Made from durable polymer, it is easy to use and comfortable to hold.

2WA 2 Wheeled Applicator

This lightweight steel applicator takes 750ml Stripeline cans and, with easy trigger activation, applies a consistent spread of paint with good line definition for straightforward line marking.

4WA 4 Wheeled Applicator

The sturdy construction of this applicator makes it easy to apply steady line marking with clear line definition using Stripeline, with easy trigger activation.







Bulk Lubrication

TYGRIS lubricants and cleaners have been developed to perform both effectively and consistently, even in the most demanding applications or under the most extreme conditions.

Make TYGRIS your #1 choice

for all your lubrication and cleaning needs!



Section 2

	Speciality Lubricants	40
37	Industrial Lubricants	44
dilit	Metal Working & Fabrication	48
8	Anti-Seize Compounds	50
0	Anti-Corrosion Fluids	52
	Industrial Cleaners & Degreasers	54
6	Greasing Equipment	56



Spotlight on... Speciality Lubricants

TYGRIS specialist greases are designed for applications subjected to, but not restricted to, low or high temperatures and extreme pressures or conditions. Our greases offer high chemical and corrosion resistance and deliver a superior, yet affordable, solution for all your grease needs.

SILIXIS+

High performance silicone grease

TG6301 1Kg

TYGRIS SILIXIS+ is a high performance, wide temperature, non-toxic lubricant for bearings, plastics and rubber parts under light to moderate loads. This special silicone oil-based, lithium complex-thickened grease is used in rubber and o-ring assembly and to lubricate ball bearings in electric motors, fans (refrigeration, oven, preheater) dryers and conveyor systems.

- Formulated to provide long service life in high temperature bearings, with extended relubrication intervals
- Reduced carbon deposits compared to conventional high temperature bearing greases
- Chemical, moisture and oxidation resistant
- Compatible with most plastics and rubber components







Chassis Grease 000

High performance chassis grease

TG7625 25Ltr

TYGRIS TG7625 is a premium grade, water resistant grease for use in heavy haulage where the presence of water and humid atmospheres can affect lubricating performance and be detrimental to the protection of parts from corrosion. TYGRIS TG7625 is specifically designed for applications where central lubrication systems are fitted onto heavy goods vehicles for chassis lubrication. This grease is deliberately designed to be softer than an NLGI No. 000 grease to provide excellent pumpability even at sub-zero temperatures.

Benefits:

- · High degree of water resistance
- Excellent corrosion prevention
- Excellent pumpability even at low temperatures
- Red colour for easy identification and traceability
- Temperature range -25°C to +80°C



Electrical Conductive Compound

Maximum protection for electrical applications

TG7412 12.5kg

TYGRIS TG7412 is a premium quality graphite compound for electrical conductive applications.

Benefits:

- Allows current to flow between two components
- · Prevents seizure and galling during assembly of components reducing assembly time
- · Enables quick dismantling of components saving on maintenance time
- Enables parts to be reused after dismantling so reducing the cost of replacing components



Heavy Duty Open Gear Grease

Highly effective lubrication & corrosion prevention

TG7712 12.5ka

TYGRIS TG7712 is a special soap complex thickened grease combining extreme pressure additives. antioxidants and corrosion inhibitors, to provide highly effective lubrication with excellent corrosion prevention. Specially developed for the lubrication of all types and sizes of open gears, including spur, helical and bevel drive gears that are subjected to extreme loads, high working temperatures and water saturated conditions. Also suitable for the lubrication of hydraulic hammers and booms.

Benefits:

- · Easy to apply in all weathers can be applied to wet surfaces
- · Bitumen free
- Withstands pressures up to 7,000kg/cm² (100,000 psi) which reduces wear
- · Long lasting, almost dry, lubricating film does not collect dust and dirt
- · Does not drip or fling off maintains a clean surrounding work area



Winch Gear Low Temp Grease

Highly water resistant grease

TG9718 18kg

TYGRIS TG9718 is a high performance, lowtemperature, winch gear grease with extreme water wash off resistance, high load bearing and anti-corrosion capabilities. Highly versatile lubricant, ideally suited to applications in extreme conditions where operating temperatures can be sub-zero.

Benefits:

- Extends lubrication intervals ensuring maximum cost savings in grease consumption
- · Very high water resistance and corrosion
- Excellent EP performance provides protection against premature wear
- Temperature range -30°C to +150°C (continuous), +200°C (intermittent)



Water Resistant Hub Grease

Highly water resistant lubricant for wheel bearings

TG9805 500a

TYGRIS TG9805 is a high performance, water resistant, hub grease with extreme water wash off resistance, high load bearing and anti-corrosion capabilities, which help extend relubrication periods and reduce maintenance costs. Designed for the use on trailer hubs and other areas where exposure to severe elements can cause premature wear.

Benefits:

- Extends lubrication intervals ensuring maximum cost savings in grease consumption
- Very high water resistance and corrosion prevention
- Excellent EP performance provides protection against premature wear
- Temperature range -30°C to +150°C (continuous), +200°C (intermittent)



Calcium Sulphonate Grease

Highly water resistant grease for use in extreme environments

TG9804 400a **TG9818** 18ka

TYGRIS Calcium Sulphonate Grease is a superior grade, extremely stable, lubricant with exceptional load carrying capacity, designed to extend relubrication intervals in a wide range of applications including those in extreme working conditions. Suitable for use in all types of antifriction, plain bearings and sliding surfaces.

- Extends lubrication intervals ensuring maximum cost savings in grease consumption
- Exceptional water resistance and corrosion prevention
- Excellent EP performance provides protection against premature wear
- Temperature range -30°C to +150°C (continuous), +200°C (intermittent)

Speciality Lubricants



WR2 Calcium Grease

Water resistant grease for industrial and marine applications

TG7204 400g **TG7205** 500g

TYGRIS WR2 Calcium Grease is a premium quality, water resistant grease for use in industrial and marine applications where the presence of water and humid atmospheres can effect lubricating performance and be detrimental to the protection of parts from corrosion. Suitable for plain and antificition bearings.

Benefits:

- · High degree of water resistance
- · Excellent corrosion protection
- · Good sealing properties



Very High Temperature Grease

Synthetic based graphite grease for very high temperature applications

TG8704 400g **TG8730** 3kg

TYGRIS Very High Temperature Grease is an industrial, extreme temperature, medium consistency grease for use at temperatures of up to 600°C in applications such as oven and kiln car bearings and in furnace door and drying tunnel mechanisms. At very high temperatures, the synthetic based liquid phase evaporates, leaving a dispersion of graphite particles to reduce wear without leaving abrasive carbon ash deposits.

Benefits:

- · No carbonisation at high temperatures
- · Extends component life at high temperatures
- · Graphite lubricating film reduces wear
- Synthetic fluid evaporates cleanly
- Classified as non hazardous



BE-100 Rope Lubricant 00

Environmentally-responsible lubricant

TG7818 18kg

TYGRIS TG7818 is a biodegradable, solvent free, semi-fluid wire rope lubricant designed to meet the lubrication and corrosion prevention requirements of wire ropes working under all conditions. Typical application areas are dockside cranes, draglines, water treatment and situations where a biodegradable lubricant is preferred for environmental reasons. TG7818 biodegrades naturally, providing a more environmentally friendly solution when compared to conventional rope lubricants.

Benefits:

- Biodegradable environmentally acceptable
- Excellent protection internally and externally extending rope service life
- Molybdenum disulphide reduces wear between strands
- Water repellent extends service intervals
- Thin film eliminates fling off and does not attract dirt
- Significant application coverage economic to use



Wire Rope Grease 000

Superior wire rope lubricant & protectant

TG9112 12.5kg

TYGRIS TG9112 is a semi-fluid grease designed to meet the extreme lubrication and corrosion prevention requirements of wire ropes working under extreme conditions TG9112 penetrates between the rope strands to provide integral lubrication and also internal and external protection against corrosion caused by moisture, adverse weather conditions and sea water.

Benefits:

- Solid lubricant reduces wear between the strands of the rope
- Water resistant film ensures long film life extending lubrication intervals
- Thin film eliminates product accumulation and does not collect abrasive particles
- Ropes are clean to handle and allow easy inspection
- Significant application coverage economic to use
- Temperature range -20°C to +120°C



High Temperature Grease

Synthetic grease for high temperature applications

TG8504 400q

TYGRIS TG8504 is a premium quality lithium complex thickened grease for use in plain and anti-friction bearing surfaces in high temperature applications over long periods of time without leaving a dry residue. Providing excellent lubrication also at subzero and ambient temperatures, this is an extremely versatile grease.

Benefits:

- High temperature resistance with extended lubrication intervals
- Reduces carbon deposits at high temperatures
- Extreme pressure additives and PTFE for long component life
- · Excellent corrosion and humidity resistance
- Temperature range -50°C to +220°C



High Speed Grease 2

Very high speed bearing grease

TG7304 400q

TYGRIS TG7304 is a premium grade lubricant pecifically designed for very high speed anti-friction bearings. Suitable for applications in the textile spinning industry; for high speed spindles on CNC machines and wood turning equipment. TYGRIS High Speed Grease 2 can, in many cases, replace oil mist lubrication systems, thus providing a cleaner and more economical method of lubrication

- Withstanding extremely high speeds, the grease stays in place and therefore prolongs lubrication intervals
- Corrosion inhibitors protect components operating in very humid environments
- Anti-wear properties provide protection against premature wear





Silicone Paste

Silicone based multi-purpose grease

TG8605 500q **TG8650** 5kg TG8620 20kg

TYGRIS' WRAS-approved Silicone Paste is used in the assembly and lubrication of taps, valves, elastomer seals and O-rings including applications working under vacuum. The superior water-repellent properties of silicone paste provides excellent water washout resistance, and is ideal for industrial and laboratory lubrication applications.

Benefits:

- · Resistant to chemical agents, solvents and oxidation - remains unaltered by mineral and vegetable oils
- Highly water repellent resists well to water
- Chemically inert; non corrosive on metals no plasticising effect on rubbers or plastics
- Very little variation in viscosity with fluctuations of temperature
- Operating temperature range between -50°C and +200°C in continuous use, and above 200°C when exposed for short periods



Silicone Valve Seal

Specialist valve lubricant and sealing compound

TG8630 3kg

TYGRIS TG8630 is a WRAS-approved silicone compound for the lubrication of valves and stopcocks in gas and water systems over a wide temperature range. It is resistant to many organic chemicals, hot and cold water, low pressure steam and many gases. It also provides lubrication and protection for O-rings.

Benefits:

- · Resistant to a wide range of different chemicals
- Due to thixotropic nature the compound thickens up after movement to ensure excellent sealing
- Protects components from corrosion and seizure
- Temperature range -40°C to +200°C



Silicone Oil F100

Specialist release agent and lubricant

TB7825 25kg

TYGRIS TB7825 provides a non-toxic, noncarbonising, mould release for rubber, plastics and metal die-castings, anti-foam agent. Very small quantities of the fluid are very effective as a foam control agent especially in non-aqueous systems. The very high viscosity index coupled with thermal and chemical stability, shear-breakdown resistance and rubber compatibility, makes this fluid ideal for mechanical and hydraulic uses, and provides excellent lubrication for most plastic and elastomeric surfaces.

- Minimal change in physical properties over a wide temperature range, remaining thermally stable at 150°C for extended time intervals
- · Low surface tension
- The fluid readily wets clean surfaces to impart water repellency and release characteristics



Spotlight on... Industrial Lubricants

All TYGRIS Industrial grade lubricants are designed to do the job first time, every time –each and every one backed by our TYGRIS 4Life guarantee.

All products are based on proven formulations, providing costeffective, fit-for-purpose, solutions to the everyday needs and challenges of industry – regardless of sector. Available in a wide range of sizes to suit all your lubrication requirements.

Lithium Moly Grease

Extreme pressure molybdenum grease

TG8304 400g | **TG8305** 500g | **TG8312** 12.5kg

TYGRIS Lithium Moly Grease is a specially developed lithium complex grease, fortified with molybdenum disulphide (MoS2) solid film lubricant for applications where the grease is required to cope with more arduous conditions, such as high loads, shock loading, wet and temperature extremes. Lithium moly grease is designed for plain as well as anti-friction bearings.

- Exceptional mechanical stability extends re-lubrication intervals
- Good oxidation stability provides lasting lubrication at high temperatures
- High degree of corrosion resistance protects components operating in wet conditions
- Extreme load carrying and impact resistance properties prolongs component life
- Temperature range -20°C to +150°C (continuous), +180°C (intermittent)







EPO/EP00/EP000 Lithium Grease

Multi-purpose grease

TG9212 EP0 12.5kg **TG9312 EP00** 12.5kg **TG9412 EP000** 12.5kg

TYGRIS lithium grease is a premium quality multipurpose semi fluid grease for use in all anti-friction and plain bearings subjected to high load conditions. The incorporation of extreme pressure and anti-wear additives imparts a high degree of wear protection against load. Used extensively for applications throughout industry and the automotive sector.

Benefits:

- Excellent extreme pressure and anti-wear performance
- · High degree of corrosion protection
- Highly versatile multi-purpose grease
- Excellent pump-ability for centralised lubrication systems
- Temperature range -20°C to +140°C



L2 GP Lithium Grease

General purpose lithium grease

TG7550 50kg

TYGRIS TG7550 is a premium quality general purpose grease for use in all anti-friction and plain bearings subjected to high load conditions. The incorporation of oxidation and rust inhibitors provides good corrosion protection and long life. Used extensively for applications throughout industry and the automotive sector.

Benefits:

- · High degree of corrosion protection
- Highly versatile general purpose grease
- Temperature range -20°C to +120°C



EP2 Lithium Grease

Multi-purpose grease

TG8404 400g

TG8405 500g

TG8430 3kg

TG8412 12.5kg

TG8418 18kg

TG8450 50kg

TYGRIS EP2 Lithium Grease is a premium quality multi-purpose grease for use in all anti-friction and plain bearings subject to high load conditions. Used extensively for applications throughout industry and the automotive sector.

Benefits:

- Excellent extreme pressure and anti-wear performance
- · High degree of corrosion protection
- · Highly versatile multi-purpose grease
- Temperature range -20°C to +140°C



EP3 Lithium Grease

Premium quality multi-purpose grease

TG8804 400g **TG8812** 12.5kg

TYGRIS EP3 Lithium Grease is a premium quality multi-purpose grease for use in all anti-friction and plain bearings subjected to high load conditions. The incorporation of extreme pressure and anti-wear additives provides a high degree of wear protection against load. Used extensively for applications throughout industry and the automotive sector.

Benefits:

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- · Highly versatile multi-purpose grease
- Temperature range -20°C to +140°C



Lithium PB Advanced

Heavy Duty Pin and Bush Lubricant

TG6004 400g **TG6012** 12.5kg

TYGRIS Lithium PB Advanced is a tenacious grease designed for heavy duty applications where adhesion, shock loading and good corrosion protection is required. It has been proven ideal for use on bucket pins on heavy earth moving equipment, fifth wheels, crane slews, and also as an assembly and running in compound.

Benefits:

- A high level of lubricating solids keeps working surfaces apart and substantially extends component life.
- Fully water resistant to extend the life of the lubricant and protect components from corrosion.
- Adhesive properties provide increased lasting protection.



Penetrating Oil

Powerful penetrant for releasing seized components

TB6205 5Ltr

TYGRIS TB6205 is a fast acting and efficient agent for the freeing of components that have become 'frozen' as the result of rust or corrosion. It is a combination of highly effective wetting and penetrating agents with solvents and low viscosity lubricating oil.

- Rapidly penetrates the finest clearances and cuts through rust and corrosion
- If a drop of the fluid is placed on a rusted surface the penetration and spreading, even in a vertical direction, will be observed immediately
- The fluid will readily free nuts, bolts, screws, locks, hinges and all threaded joints
- Anything that resists the action of a spanner or screwdriver should be treated with P & R Fluid, and left for a few minutes to allow penetration after which it can be readily released





Red Lithium Complex Grease

Superior lubricant for demanding applications

TG9004 400g **TG9012** 12.5kg

TYGRIS Red Lithium Complex Grease is a specially developed multi-purpose lithium complex grease for lubricating all types of anti-friction and plain bearings in industrial and automotive applications. This grease is highly effective at providing extended lubrication intervals over a wide operating temperature range.

Benefits:

- Exceptional mechanical stability extends lubrication intervals
- Excellent oxidation stability provides lasting lubrication at high temperatures
- Excellent extreme pressure and anti-wear performance
- High corrosion resistance protects components operating in wet conditions
- Temperature range -20°C to +150°C



White Lithium Grease

Versatile multi-purpose grease

TG8430W 3kg

TYGRIS White Lithium Grease is a high quality multi-purpose white grease enhanced with a specially selected water repellent additive for use in applications requiring extreme water resistance. Used extensively for applications throughout industry, marine and the automotive sector; in anti-friction and plain bearings, and pumping equipment where ingress of water can be detrimental to lubrication.

Benefits

- Versatile multi purpose grease
- Excellent water resistance
- Excellent corrosion protection
- Good sealing properties
- Temperature range -20°C to +140°C



Blue Lithium Complex Grease

Superior lubricant for demanding applications

TG8904 400g

TG8905 500g

TG8912 12.5kg

TYGRIS Blue Lithium Complex Grease is a specially developed multi-purpose lithium complex grease for lubricating all types of anti-friction and plain bearings in industrial and automotive applications. This grease is highly effective at providing extended lubrication intervals over a wide operating temperature range. Extensively used in plant and machinery applications.

- Excellent oxidation stability provides lasting lubrication at high temperatures
- Excellent EP and anti-wear performance
- High corrosion resistance protects components operating in wet conditions
- Temperature range -20°C to +150°C



PROTEAN ASSURED...

Site Visits
 Lubrication Needs Assessments
 Bespoke Storage Solutions
 Real-time Support
 Audit Compliance
 Assurance Guaranteed...

A Complete 'Food Safe' Solution

Ungated online access to critical infomation

Unlike some of our competitors, we avoid the hurdles of having to register and login in order to access key essential information such as product safety data sheets, offering mobile friendly, real-time information 24/7/365.



PROTERIO Essential Nutrition for Industry



www.tygrisindustrial.com


TYGRIS

Bespoke audit compliance folders

Personalised folders bearing end-user and distributor logos. These are printed inhouse and shipped FOC within 3 business days of initial request. Folders contain both safety and technical data sheets, NSF/Ins Certificates, Allergens Statements and even a PROTEAN pad and pen.

Storage solutions

- Medium duty steel construction – quality by design
- Custom-wrapped with optional distributor branding
- Highly customisable to suit the needs of the end-user



Spotlight on... Metal Working & Fabrication

TYGRIS metal working products are reinforced with extreme pressure additives, yielding high film strength and anti-weld properties that effectively extend tool life and improve surface finish.

Metal Working Paste

Fortified cutting and tapping compound

T500 450q

TYGRIS T500 is a soft paste which has been reinforced with the most effective extreme pressure additives to give high film strength and anti-weld properties which are essential to counter the pressure developed during metal working. It can be used with hard metals to reduce heat and improve the dimensional stability of the surface finish. Designed for cutting, tapping, drilling, reaming, drawing, pressing, extruding and forming.

- Effective on stainless steel and light alloys
- Extreme pressure additives
- Extends tool life
- Fortified with molybdenum
- Improves surface finish
- Greater dimensional accuracy
- Non hazardous







Metal Working Fluid

Fortified with molybdenum

T510 350ml bottle **T515** 5Ltr

TYGRIS Metal Working Fluid is an organic oil which has been reinforced with the most effective extreme pressure additives to give high film strength and anti-weld properties which are essential to counter the pressure developed during metal working. It can be used with hard metals to reduce heat and improve the dimensional stability of the surface finish. Designed for forming, cutting, tapping, drilling, reaming, drawing, pressing and extruding.

Benefits:

- Effective on stainless steel and light alloys
- Extreme pressure additives
- Extends tool life
- · Fortified with molybdenum
- · Improves surface finish
- · Greater dimensional accuracy
- Non hazardous



Metal Working Spray

Penetrating cutting enhancer and cooling agent for hard metals

R208 400ml

TYGRIS R208 Metal Working Spray has been developed specifically to meet the cutting lubrication demands of harder metals such as stainless steel. Its enhanced extreme pressure additives and non-solvent, high mineral oil contents make R208 a consistently high performing lubricant which cools and penetrates to enable a clean cutting action and increase tool life.

Benefits:

- · Proven performance on stainless steel
- · Fast flowing and penetrating formula
- · Solvent free
- Enhanced extreme pressure additives
- Developed for hard materials
- · Suitable for cutting, tapping, drilling and reaming
- Reduces heat build up
- · Prolongs tool life and improves machined finish



Cutting and Tapping Fluid

Contains extreme pressure additives to reduce tool wear and improve machined finish

R214 400ml

TYGRIS R214 is a ready to use cutting and tapping fluid specially formulated to improve tool performance and extend tool life. It contains additives to prevent pitting, galling and metal seizure and is suitable for use on hard to work metals including stainless steel, titanium, aluminium and tool steel.

Benefits:

- For cutting, tapping, reaming and turning
- Extreme pressure additives for difficult materials
- High pressure, frothy discharge to aid penetration
- Prolongs tool life and improves machined finish
- Reduces heat build up
- · Suitable for use on all metals
- Incorporates corrosion inhibitors



Weld Spatter Release Spray (Solvent Based)

Non-silicone weld spatter release spray

R221 400ml

TYGRIS R221 is a special non-silicone formulation ideal for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools and enables free gas flow in inert gas welding.

Benefits:

- Non-silicone can be used with products that require finishing
- · Rapid drying
- Prevents adhesion spatter easily removed
- Colourless non-staining
- · Does not gum up when subject to heat
- · Non-flammable for maximum safety



Weld Spatter Release Spray (Water Based)

Non-silicone, non-flammable weld spatter release spray

R222 400ml

TYGRIS R222 is a water based solvent-free formulation for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools. Its water based properties offer an environmentally friendly alternative to solvent based varieties.

Benefits:

- · Prevents spatter adhesion
- Non-silicone can be used with products that require finishing
- · Excellent non-stick finish
- Non-flammable
- · Water rinseable
- · Dichloromethane free



Ceramic Release Spray

Release spray for use on welding torches and extrusion dies

IS35 400ml

TYGRIS IS35 is a ceramic/boron nitride spray for use as a dry film protective coating on MIG welding torches, jigs, fittings and cables etc to prevent the adhesion of welding spatter. Also used as an excellent lubricant on moulds and dies used in aluminium extrusion processes.

- Protects welding torches, jigs and fixtures from welding spatter reducing downtime costs
- Physical barrier protects surfaces from heat
- Extends shroud service life
- Safe for use on metal components, cables and sensors
- Easy to apply with excellent adhesion
- Silicone free so compatible with post finishing processes
- Application only required once or twice a shift

Spotlight on... Anti-Seize Compounds

TYGRIS anti-seize compounds provide outstanding metal protection up to temperatures of 1100°C to enable quick and easy dismantling of components.

Copper A-S Advanced

High temperature anti-seize protection up to 1100°C

R234 400ml

TYGRIS R234 is a high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. Resistance to water and acids is high and it will not burn off under extreme stress. For use on threaded components, pins, valve stems in a range of materials including austenitic stainless steel. Used on brake callipers and the back of brake pads it will help eliminate brake squeal.

- Effective up to 1100°C
- Water and acid resistant
- · Use on a wide range of metals
- Prevents seizure of threaded parts
- · Will not burn or wash off
- Eliminates brake squeal
- · Assists in assembly and disassembly of components







Copper Anti-Seize Compound

High temperature anti-seize protection

TG8205 500q

TYGRIS TG8205 is a high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. High resistance to water and acids and does not burn off under extreme stress. For use on threaded components, pins and valve stems, in a range of materials including austenitic stainless steel. Commonly used within light engineering and the automotive maintenance/repair sector.

Benefits:

- · Water and acid resistant
- Temperature range -30°C to +1100°C
- Use on a wide range of metals
- Prevents seizure of threaded parts
- · Will not burn or wash off
- Eliminates brake squeal
- Assists in assembly and disassembly of components



Aluminium Anti-Seize

High temperature anti-seize protection up to 800°C

R233 400ml

TYGRIS R233 is a high temperature multi purpose blend of heat stable lubricant and anti-seize compound used in a wide range of automotive, industrial, marine and construction applications, helping to eliminate seizure, pitting and rusting of components exposed to heat. Use on threaded components, flanges, chains and locks to facilitate in future dismantling.

Benefits:

- · Prevention of seizure
- Assists in easy dismantling of threaded parts
- Effective lubrication at ambient temperatures
- High temperature resistance to melting
- · Use also on flanges, chains and locks
- Facilitates easy re-use of dismantled components
- Temp. range: -30°C to +275°C



Aluminium Anti-Seize

High temperature anti-seize protection up to 760°C

TG8105 500g

TYGRIS TG8105 is a premium quality anti-seize compound containing soft aluminium solid lubricant. Specially developed for applications on aluminium fasteners requiring low sulphur, chlorine and fluorine levels, thus reducing corrosion. This compound is formulated to be used in extreme high temperature environments of up to 760°C and is excellent for protection of threaded connections, exposed surfaces and flanges. TG8105 is compatible with plastics and metals.

Benefits

- Prevents seizure and galling during assembly thus reducing assembly time
- Protects against pitting and therefore prolongs component life
- Prevents rusting, fretting and corrosion in exposed conditions
- Enables quick dismantling of components saving on maintenance time
- Enables parts to be reused after dismantling so reducing the cost of replacing components



ProPaste+

High performance multi-purpose lubricant

TG5905 500g **TG5918** 18kg **TG5930** 3kg

PROTEAN ProPaste+ is a NSF: H1 registered, highly versatile, multi-purpose paste for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments. With a high solids content, PROTEAN ProPaste+ provides an all-in-1 premium food grade solution for assembly, anti-seize, lubrication and pre-treatment needs, and represents the true nature and meaning of 'Protean'. Halal/Kosher Certified.

Benefits:

- NSF: H1 registered (lubricant with incidental food contact – for use in and around food processing areas)
- Exhibits excellent EP performance with a 4 ball weld load of 600kg



Nickel Anti-Seize Compound

Specialist anti-seize lubricant for extreme environments

TG8005 500g

TYGRIS TG8005 is a premium quality anti-seize compound containing nickel. Specially developed to reduce corrosion and seizure on applications requiring low sulphur, chlorine, and fluorine levels, such as on Nimonic, stainless steel and silver coated components. TYGRIS TG8005 is also formulated to be used in extremely high temperatures, up to 1420°C. TYGRIS TG8005 is excellent for the protection of threaded connections, exposed surfaces and flanges.

Benefits:

- Prevents seizing and galling during assembly and therefore reduces assembly time
- Enables the easy dismantling of components subjected to extremely high temperatures
- Chemically inert thus provides an effective antiseize in saturated chemical environments
- Enables fast and easy dismantling of components allowing them to be reused



ProPaste

High performance multi-purpose spray lubricant

F405 400ml

PROTEAN ProPaste is a spray-formulated tenacious lubricant suitable for use within Food & Beverage, Packaging, Pharmaceutical and other cleanroom environments. Engineered as an anti-seize paste, PROTEAN Propaste is ideal for the assembly and lubrication of bushes, slides, threads and small open gears and also suitable as a food grade drilling, cutting and tapping lubricant in areas where in-situ repair and maintenance is required.

- NSF registration pending
- Highly versatile tenacious lubricant, resists water wash off
- Innovative anti-seize paste for assembly and lubrication
- Suitable for use as a food grade metal working paste
- · Ideal for use on stainless steel fasteners
- 360° value for inverted use

Spotlight on... Anti-Corrosion Fluids

TYGRIS anti-corrosion fluids are designed to provide outstanding metal protection in both internal and external environments – including machinery in container transportation where high levels of condensation occur.

Water Displacing Anti-Rust Fluid

Unique formulation for demanding applications

TB6105 5Ltr

TYGRIS TB6105 is a stable solution containing sophisticated chemicals and petroleum derivatives together with lanolin, which is an excellent protective and lubricant. TB6105 does not contain silicones.

Renefits

- As well as being compatible with all hydraulic fluids, mineral and vegetable oils, the fluid leaves surfaces coated with a greasy finish which does not retain or attract dust
- When wet parts are immersed in the fluid the water separates to permit continued use of the fluid
- The film formed by the fluid is constant in thickness, regardless of the amount used, thus providing maximum surface spread
- Protects all metal surfaces against rust and corrosion, including parts kept in store for prolonged periods
- Drives out water, dries out and rapidly damp proofs all electrical systems to give safe and efficient operation
- · Penetrates and cleans corroded and rusted parts







Atmotec 50

Metal protection for medium term indoor storage

TB5105 5Ltr

Metal protection for medium term indoor storage application. Will protect bare metal for up to two years under normal storage conditions. Often doesn't need to be removed. TYGRIS TB5105 is ideally suited for the protection of machined metal parts. TYGRIS TB5105 will coat up to 120 square metres per litre.

Benefits

- · Effective for up to 2 years
- Very good coverage
- Very clean to use
- · Doesn't need to be cleaned off prior to coating



Atmotec 90

Superior metal protection for internal and external use

TB5205 5Ltr

Extreme environment metal protection for all stored metal parts, subject to a corrosive environment, including outdoor, for long periods of time where secondary protection is in place. Up to three months protection when totally exposed and at least 3 years when protected. Coverage on this product is up to 45 square metres/litre.

Benefits:

- Effective for up to 3 years
- · Very good coverage
- Very clean to use
- · Doesn't need to be cleaned off prior to coating



AtmoShield+

High performance corrosion inhibitive wax film

Nonfood Compounds Program Listed H1 Registration Number: 154794

F426 400ml

AtmoShield+ is a NSF: H1 registered spray-formulated heavy duty wax film, enriched with corrosion inhibitors and suitable for use within Food & Beverage environments. Providing long term protection against corrosion on metal components and equipment, and resistant to both water wash-off and cleaning, PROTEAN AtmoShield+ is ideal for use on machined surfaces and assemblies that are subjected to long periods of storage or shipping conditions.

Benefits

- · Corrosion inhibitors long-term metal protection
- · Clean white film for improved coverage visibility
- Tenacious heavy duty wax film resistant to wash wash-off and cleaning 360° valve for inverted use



Water Displacing Anti-Rust Agent

Displaces water, penetrates, lubricates and protects

R213 400ml

TYGRIS R213 is a high performance water displacement spray which actively drives out moisture, even from hard-to-reach areas, leaving a fine lubricating film which protects against corrosion. This film enables future dismantling of equipment. Also an effective cleaner and degreaser.

Benefits:

- · Silicone free
- Powerful water displacement properties
- Leaves a shield against further moisture ingress
- Leaves a protective film, guarding against corrosion
- Good general lubrication for most components
- · A rapid penetrant for seized fixings



De-Watering, Anti-Rust Tool Protector

Protects against corrosion for up to 2 years – indoor storage

IS3 400ml

TYGRIS IS3 is a high performance, fast drying, water displacement spray, offering both effective lubrication and medium term corrosion prevention. Use on tooling, chains, switchgear, machinery and ignition systems.

Benefits:

- Excellent water displacement chases away droplets
- Protects against rust for up to 2 years inside storage
- Can be applied to wet surfaces
- Removes moisture from ignition systems for easier starting
- Protective film is virtually transparent and removal is not normally necessary
- The dry coating meets MOD specification 68-19 (PX-24) and NATO Code C-634



WD Anti-Rust Agent

Moisture displacement spray

Nonfood Compounds Program Listed H1 Registration Number: 139267

F416 400ml

TYGRIS F416 is a PTFE based aerosol effective for use in displacing moisture and water based fluids from most surfaces, leaving a residual film of lubricant. Used on sliding surfaces, in bearings and for other light applications in food processing environments.

- H1 registered for use in food environments
- · PTFE based for effective moisture displacement
- Use for light lubrication
- · Leaves a film of lubricant
- Temp. range: -20°C to +250°C
- 360° valve for inverted use

Spotlight on... Industrial Cleaners & Degreasers

The TYGRIS range of powerful industrial cleaning and degreasing products deliver effective solutions for everyday, essential and challenging cleaning tasks.

Make TYGRIS your #1 choice for all your cleaning needs!

Industrial Cleaner Fast Drying

Fast drying solvent based cleaner which leaves no residue

R207 400ml

TYGRIS R207 is a fast drying industrial cleaner which is used to break down grease, dirt, oil and other workshop contaminants quickly and easily without the need of subsequent rinsing, saving time and maintaining a clean environment.

- Exceptional mechanical stability extends re-lubrication intervals
- Good oxidation stability provides lasting lubrication at high temperatures
- High degree of corrosion resistance protects components operating in wet conditions
- Extreme load carrying and impact resistance properties prolongs component life
- Temperature range -20°C to +150°C (continuous), +180°C (intermittent)







Brake and Clutch Cleaner

Powerful cleaning and degreasing agent

TB6005 5Ltr

TYGRIS Brake and Clutch Cleaner effectively removes oil, grease, dirt and dust from brakes and clutches, helping to eliminate brake squeal and clutch slip caused by glazing and contamination. This product can also be used on many other surfaces as a powerful cleaning agent, but not on plastic or rubber components.

Benefits:

- · Powerful cleaning and degreasing agent
- Helps eliminate brake squeal
- Assists prevention of clutch slip
- · Removes oil, grease and dirt



Electrical Degreaser

Powerful solvent blend

TB6305 5Ltr

TYGRIS TB6305 is a rapid and highly effective degreasing agent with excellent performance on all deposits of oil, grease and tar.

Benefits:

- Efficiently cleans plastics, ferrous and non-ferrous metals, evaporating rapidly to leave a clean dry surface
- Residual free
- · Medium fast evaporating



Industrial Solvent Cleaner

Powerful cleaning and degreasing agent

TB7005 5Ltr

TYGRIS Industrial Solvent Cleaner effectively removes oil, grease, dirt and dust from industrial machines and surfaces. This product can also be used on many other surfaces as a powerful cleaning agent, but not on plastic or rubber components.

Benefits:

- Powerful cleaning and degreasing agent
- Fast drying solvent formulation
- Removes oil, grease and dirt



Emulsifying Solvent Degreaser

Powerful degreasing fluid

TB8405 5Ltr

TYGRIS TB8405 is a red, low viscosity solvent cleaner containing powerful degreasing solvents and a surfactant to aid wash off. Ideal as a general purpose cleaner, which can then be rinsed off with water to leave a grease free surface. Formulated to attack the toughest grease and oil deposits, often out performing more traditional products.

Benefits:

- Suitable for most metals, concrete, tiled and plastic surfaces
- Not suitable for prolonged contact with rubber, asphalt or bitumen



HydroTough 100

Non-Toxic, Concentrated Cleaner / Degreaser

TB2005 5Ltr

TB2025 25Ltr

TYGRIS TB2005 is a safe and effective solution for tackling heavy fuel oils deposits, stubborn greases, bitumen, resins, waxes and aged oil contamination. HydroTough 100 is recommended for use by local authorities, tar manufacturers, highway maintenance companies, industrial cleaners and bioremediation solution providers.

Benefits:

- Totally safe to use and environmentally responsible
- Outlasts conventional cleaners/degreasers
- Acts as a bio-accelerator for complete breakdown of hydrocarbons
- Prevents grease and oil build up on tools, equipment and machinery
- · Extremely effective and economical in use
- Ideal for removing heavier contamination deposits
- Renders hydrocarbons non-flammable
- Aids biodegradation



HydroTough RI

Non-Toxic, Low-Vapour Cleaner / Degreaser

TB2305 5Ltr

TB2325 25Ltr

TB2305 is a safe and effective alternative to solvents or high alkaline-based detergents that are commonly used for cleaning and degreasing glass, plastics and metals (both ferrous and non-ferrous). HydroTough RI is recommended for use by manufacturers or service companies in the preparation of component parts within manufacturing or refurbishment processes.

- Totally safe to use (no caustics, chlorinated solvents, silicates or phosphates)
- Outlasts conventional cleaners/degreasers
- Contains short-term rust inhibitors
- Ideal for cleaning and brightening metals such as Aluminium and Brass
- Prevents grease, oil and sludge build up on machinery and equipment, thus reducing maintenance downtime and costs
- Aids biodegradation of greases, oils and other hydrocarbon materials
- Highly effective and economical in use and minimises expensive disposal costs

Spotlight on... Greasing Equipment

TYGRIS grease equipment provides effective solutions for applying the right TYGRIS lubricant to the right place – including the new clear vision products and automatic refillable lubricators.

Premium Side Lever Grease Gun

Heavy duty side lever grease gun

TGG502

TGG502 is a heavy duty side lever grease gun with drop resistant steel head construction. It will accept a standard 400ml cartridge and has a ram-rod system for cartridge loading, but can also be bulk or suction filled. TGG502 is supplied with a rigid 150mm extension tube and push-on 4 jaw hydraulic coupler. TYGRIS grease guns are designed to handle all TYGRIS greases to NLGI – No.2 specification.

- Develops up to 6,000 psi / 413 bar
- Screwed end cap for easy cleaning and quick discharge of empty cartridge
- Grease capacity of 500cc for bulk fill or 400g cartridge
- Bulk filler nipple/air release
- Soft rubber handle grip and knurled barrel for a firm hold







Premium Pistol Grip Grease Gun

Heavy duty pistol grip grease gun

TGG503

Ergonomic grease gun with unique variable stroke mechanism for both high volume and high pressure applications.

Benefits:

- Develops 7,000 PSI / 480 bar
- Simple adjustment lever to switch between high pressure and high volume setting
- Complete with 12" (300mm) flexible extension and professional 4 jaw coupler
- Up to 0.84 gms / stroke



Hydraulic 4 Jaw Grease Gun Coupler

TGG510

Professional hydraulic coupler. 4 jaw 1/8" BSPT thread and hex nut.

Benefits:

- Maximum pressure 6000psi 413bar
- Suitable for hand operated grease guns



Refillable Auto Bearing Lubricator

TGG511 100ml **TGG512** 220ml

High quality, mechanical, chemical and thermal resistant. Designed to provide constant lubrication to bearings, bushings, joints, articulated joints or wherever constant greasing is required, with in-built adjustable dispensing rate settings.

Benefits

- Manufactured from transparent Lexan
- Setting dial (1, 3, 6 and 12 months) supply duration
- Supplied with medium tension spring with optional light & strong tension springs available for varying applications
- Suitable for use with all types of grease NLGI 0-1-2-3-4
- Operating temperatures -30°C to +132°C



Clear Vision Lever Grease Gun

Heavy duty side lever grease gun with transparent barrel

TGG506

The 'Clear Vision' range is a unique system giving 100% user confidence in dispensing the correct grease; avoiding costly mistakes that cannot be reversed. The transparent barrel is made from a high-grade polycarbonate, that is stronger and tougher than steel. The tubes are drop and impact resistant and UV stabilized for working in practically any kind of weather.

Benefits:

- Tough and impact resistant polycarbonate barrel with die cast aluminium fittings
- Develops 5,000 PSI / 345 bar, and delivers up to 0.50 gms / stroke
- Complete with 12" (300mm) flexible extension and professional 4 jaw coupler
- · Refillable options: 400g cartridge or manual fill



Flexible Extension

Heavy-duty high-pressure flexible extensions

TGG508 300mm **TGG509** 500mm

Heavy-duty high-pressure flexible extensions, suitable for both hand and air operated grease guns. Fitted with 1/8" BSPTM ends.

Benefits:

 Superior construction – inner tubing is polyamide with polyurethane sheathing, reinforced diagonally in highly tear resistant polyester

ZGH300

- Length (end To end) 12" 300mm
 ZGH500
- · Length (end To end) 20" 500mm
- Working pressure: 5,800 PSI (400 bar)
- Warning: Never use beyond recommended working pressure
- Assists in assembly and disassembly of components



Clear Vision Pistol Grip Grease Gun

Heavy duty pistol grip grease gun with transparent barrel

TGG507

Pistol-grip alternative of TGG506, providing 100% user confidence in dispensing the correct grease. Helps avoid costly mistakes that cannot be reversed

Benefits:

- Develops 10,000 PSI / 690 bar variable stroke feature built in for use in confined areas
- Heavy-duty grease gun head incorporates a bulk loader and an air bleeder valve
- Unique lock lever mechanism allows user to easily lock plunger rod in any position
- 1 gm / stroke
- Complete with 6" (150mm) steel extension and professional 4 jaw coupler
- Refillable options: 400g cartridge, bulk or manual fill



Hand Operated Oil Pump

Oil transfer equipment – hand operated pumps

TGG521

Economy oil pump suitable for 20 litre containers.

Benefits:

- · Built in oil drain back facility
- 1.5 m anti-kink hose
- Non-drip dispensing nozzle
- Delivers approximately 65 mL (14 strokes per litre) on the down stroke
- Suitable for oils and non-corrosive liquids up to SAE140



Grease Nipple Assortment Packs

TGG514 Metric – 80pcs

TGG513 BSPT – 50pcs



A. Wheeled Application 3.7 Long Mode May be designed application 3.7 Cap 20 Food Side Labelance 3.2 25.0 SLIP Application 1.5 Application <	Code D	Description	Page	Code I	Description	Page	Code I	Description	Page	Code D	escription	Page
4-Wile of Application 37 LUOS Line Marker Orange 37 RZD Chain Extinct Uniform 20 Assist Remover Tipo 420 Calce Remover Tipo 7 4-02 White Grease 2.4 UNU Universative Red 37 RZD Wed Spatter Seless Stray 2.4 ± 20 Most Control Ways 2.7 Most Control Research 7 RZD Wed Spatter Release Stray 2.4 ± 20 Most Control Ways 2.7 RZD Most Strate Release Stray 2.4 ± 20 Most Control Ways 2.7 RZD Most Strate Release Stray 2.4 ± 20 Most Mark Strate Release Stray 2.4 ± 20 Most Strate Release Stray 2.4 ± 20 Most Mark Strate Releases Stray 2.4 ± 20 Most Mark Strate Releases Stray 2.4 ± 20 Most Mark Strate Releases	2WA	2 Wheeled Applicator	37	LMGN	Line Marker Green	37	R219	Food Safe Lubricant	23	R267	Sticky Label Remover	15
Fast Dry Solvent Cheaner 10		• •									·	
Multi-Liube	F400	Fast Dry Solvent Cleaner	10	LMRD	Line Marker Red	37	R221	Weld Spatter Release Spray	29, 49	R270	Dashboard Cleaner Non-Silicone	7
Probate Prob		•	24	LMW	Line Marker White	37				R273		20
Math		Multi-Lube	24	LMY	Line Marker Yellow	37	R222	Weld Spatter Release Spray	29, 49	R274	•	
Prof. Prof	F405	ProPaste	24, 51	P300	Matt Black Paint - RAL 9005	36		(Water Based)		R275	Seize Release Penetrating Oil	20
Metal Working Fluid 49 4930 69 58 50 Fazz 40 50 50 50 50 50 50 50	F406	Electrical Cleaner	10	P301	Satin Black Paint - RAL9005	36	R223	White Grease with PTFE	22	T500	Metal Working Paste	48
Prof. Prof	F408	Chain Spray	24	P302	Gloss Black Paint - RAL9005	36	R224	Bright Zinc Galve Spray	34	T510	-	49
Felle Ward-Neur Agent 25, 53 9305 Red Oxide Primer 36 R229 Clear Polymer Chain Lubricant 20 T8203 HydroTough R1 55	F410	PTFE Dry Film Lubricant	24	P303	Grey Primer	36	R225	Non-Silicone Mould Release Agent	26	T515	Metal Working Fluid	49
No.	F412	Penetrating Oil	24	P304	White Primer	36	R226	Clear Grease	23	TB2005	HydroTough 100	55
Strick teases 25 25 25 25 25 25 25 2	F416	WD Anti-Rust Agent	25, 53	P305	Red Oxide Primer	36	R227	Rapid De-Icer Water Free	29	TB2025	HydroTough 100	55
Samins Gleaner 10 P308 Black Primer 36 R230 Clear Silicone Crease 23 T8505 Atmotec 90 53	F418	Silicone Release	25	P306	Gloss White Paint - RAL9003	36	R228	Clear Polymer Chain Lubricant	20	TB2305	HydroTough RI	55
Feature Feat	F420	Stainless Steel Cleaner	10	P307	Bright Silver Paint - RAL9006	36	R229	Drive and Bearing Lubricant	21	TB2325	HydroTough RI	55
Falson F	F422	Foaming Cleaner	10	P308	Black Primer	36	R230	Clear Silicone Grease	23	TB5105	Atmotec 50	53
Fals State	F424	Label Remover	10	P309	Self-Etching Primer	36	R232	Super Lube Extreme Pressure	21	TB5205	Atmotec 90	53
Falso Fal	F426	AtmoShield+	33, 53	P310	Gloss Blue Paint - RAL5010	36	R233	Aluminium Anti-Seize	22, 51	TB6005	Brake and Clutch Cleaner	55
F435 3H1 Grease (Spray) 25 P312 Gloss Red Paint - RAL13000 36 R235 Electrical Cleaner 8 T86205 Penetrating Oil 45	F428	Seize Release+	25	P311	Gloss Green Paint - RAL6001	36	R234	Copper A-S Advanced	22, 50	TB6105	Water Displacing Anti-Rust Fluid	52
Fals 3H1 Fluid (Spray) 25 P313 Gloss Yellow Paint - RAL1007 36 R236 R236 Leak Detector 28 TB6305 Electrical Degreaser 55 HHA Hand Held Applicator 37 P314 Gloss Orange Paint - RAL2004 36 R237 P715 P715 P715 P716 Discos Orange Paint - RAL2005 36 R239 Zinc Galvanising Spray Heavy Duty 34 TB7825 Silicone Dil 170 43 HW111 Engineer's Wijes 17 P320 Varispray Custom Colour service 36 R240 Circuit Freezer Spray (Low CWP) 29 TB8405 Silicone Dil 170 M3 HW111 Engineer's Wijes 17 P320 Varispray Custom Colour service 36 R240 Circuit Freezer Spray (Low CWP) 13 TC011 Bright Zinc Cold Galvanize 34 HS13 Mould Release Heavy 26 P334 Aluminium VHT Paint 36 R242 Clear Acrylic Lacquer 33 TC204 GalvShield + 34 HS13 Mould Release Non-Silicone 26 R199 Dashboard Renovator Cherry 7 R244 Clear & Anti-Static Foraming Gleaner 17 TC219 GalvShield + 34 HS25 Electro Clean 8 R201 Carburettor Cleaner 7 R246 Clean & Polish 16 TG5905 ProPaster 51 HS25 Mould & Tool Cleaner Stra 17 R202 Brake and Clutch Cleaner 7 R246 Clean & Polish 16 TG5905 ProPaster 51 HS27 Mould & Tool Cleaner Supa 17 R202 Brajne Degreaser 7 R248 Alf Freshener Cranberry 13 TG5918 ProPaster 51 HS33 De-Watering, Anti-Rust 19, 53 R204 Battery Terminal Protector 33 R249 Alf Freshener Cranberry 13 TG5910 ProPaster 51 HS35 Ceramic Release Spray 23, 49 R206 Dashboard Renovator Cranberry 7 R251 Graffitt Remover 14 TG7205 WR2 Calcium Grease 42 HS45 Synthetic Ejector Pin Lubricant 26 R207 Industrial Cleaner Fast Drying 8, 54 R252 Graffitt Remover Citrus Based 14 TG7205 WR2 Calcium Grease 42 HS56 Clear Mould Protector 33 R210 Heavy Duty Adhesive 28 R255 Mould Release Medium 26 R213 Water Displacing Anti-Rust 19, 53 R254 High Wax Polish 14 TG7205 Keed Grease 2 4	F430	3H1 Grease (Spray)	25	P312	Gloss Red Paint - RAL3000	36	R235	Electrical Cleaner	8	TB6205		45
HAM Hand Held Applicator 37 P314 Gloss Orange Paint - RAL2004 36 R237 PTE Dry Film Lubricant 22 T87005 Industrial Sowent Cleaner 55	F435	3H1 Fluid (Spray)	25	P313	Gloss Yellow Paint - RAL1007	36	R236	Leak Detector	28	TB6305	•	55
HW111 Engineer's Wipes 17 P320 Varispray Custom Colour service 36 R240 Circuit Freezer Spray (Low GWP) 29 T88405 Emulsifying solvent Degreaser 55		* * */	37	P314		36	R237	PTFE Dry Film Lubricant	22		=	55
HW111 Engineer's Wipes 17 P320 Varispray Custom Colour service 36 R240 Circuit Freezer Spray (Low GWP) 29 TB8405 Emulsifying Solvent Degreaser 55	HW101	OneWipe™	12, 17	P315	Gloss Dark Green Paint - RAL6005	36	R239	Zinc Galvanising Spray Heavy Duty	34	TB7825	Silicone Oil F100	43
STO Looz-n-It Penetrating Oil 19 P330 Black VHT Paint 36 R241 Micro Air Duster (Low CWP) 13 TC101 Bright Zinc Cold Galvanize 34	HW111	Engineer's Wipes	17	P320	Varispray Custom Colour service	36	R240	Circuit Freezer Spray (Low GWP)	29	TB8405	Emulsifying Solvent Degreaser	55
Mould Release Non-Silicone 26 R199 Dashboard Renovator Cherry 7 R245 Anti-Static Foaming Cleaner 13 TC208 Gal/Shield + 34	IS1	· ·	19	P330	Black VHT Paint	36	R241	Micro Air Duster (Low GWP)	13	TC101		
Solvent Tool & Electronics Cleaner 8 R200 Dashboard Renovator Apple 7 R245 Anti-Static Foaming Cleaner 17 TC219 GalvShield + 34	IS10	Mould Release Heavy	26	P334	Aluminium VHT Paint	36	R242	Clear Acrylic Lacquer	33	TC204	GalvShield +	34
Section Sect	IS13		26	R199	Dashboard Renovator Cherry	7	R244	Glass & Mirror Cleaner	13	TC208		34
Second S	IS2	Solvent Tool & Electronics Clean	ier 8	R200	Dashboard Renovator Apple	7	R245	Anti-Static Foaming Cleaner	17	TC219	GalvShield +	34
Size Mould & Tool Cleaner Supa 17 R203 Engine Degresser 7 R248 Air Freshener Cranberry 13 TG5930 ProPaster 51	IS20	Electro Clean	8	R201	Carburettor Cleaner	7	R246	Clean & Polish	16	TG5905	ProPaste+	51
Section Sect	IS25	Mould & Tool Cleaner Xtra	17	R202	Brake and Clutch Cleaner	7	R247	Shoe & Helmet Sanitiser	16	TG5918	ProPaste+	51
Tool Protector Red Dashboard Renovator Cranberry 7 R250 Barrier Cream 14 TG7204 WR2 Calcium Grease 42 ISS5 Synthetic Ejector Pin Lubricant 26 R207 Industrial Cleaner Fast Drying 8, 54 R252 Graffiti Remover Viscous 14 TG7205 WR2 Calcium Grease 42 ISS6 Clear Mould Release Medium 26 R208 Metal Working Spray 23, 49 R253 Hard Surface Foam Cleaner 14 TG7304 High Speed Grease 2 42 ISS6 Clear Mould Protector 33 R209 Graphited Penetrating Oil 19 R254 High Wax Polish 14 TG7304 High Speed Grease 2 42 ISS7 Green Mould Protector 33 R210 Heavy Duty Adhesive 28 R255 Ink & Gum Remover Citrus Based 14 TG7505 L2 GP Lithium Grease 44 ISS7 Synthetic Chain Lubricant 20 R211 Clear Fine Oil 19 R258 Stainless Steel Cleaner 15 TG7625 Chassis Grease 000 41 ISS9 Mould Release Light 26 R213 Water Displacing Anti Rust Agent 19, 53 R260 Heavy Duty Adhesive 28 R255 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 ISS9 Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 ISS9 Crack Detector Developer No. 3 28 R215 Belt Dressing Anti-Slip 21 R266 Chewing Gum Remover 16 TG8205 Copper Anti-Seize Compound 51 ISS9 Crack Detector Developer No. 3 28 R216 Open Gear Lubricant 22 R266 Green Maisture Guard 33 R276 Lithium Moly Grease 44 ISS9 Green Maisture Guard 34 ISS9 Creen Maisture Guard 34 ISS9 Creen Maisture Guard 35 ISS9 Creen Maisture Guard 37 R217 Silicone Lubricant 22 R266 Green Maisture Guard 37 R217 Silicone Lubricant 22 R266 Green Maisture Guard 38 Issael Line Marker Blue 37 R217 Silicone Lubricant 22 R266 Green Maisture Guard 37 R217 Silicone Lubricant 22 R266 Green Maisture Guard 38 R276 Lithium Moly Grease 44 R250 R251 Graen Maisture Guard 38 R250 Lithium Moly Grease 44 R250 R250 R251 Lithium Moly Grease 44 R250 R251	IS27	Mould & Tool Cleaner Supa	17	R203	Engine Degreaser	7	R248	Air Freshener Cranberry	13	TG5930	ProPaste+	51
IS35 Ceramic Release Spray 23, 49 R206 Dashboard Renovator Lemon 7 R251 Graffiti Remover 14 TG7204 WR2 Calcium Grease 42 IS45 Synthetic Ejector Pin Lubricant 26 R207 Industrial Cleaner Fast Drying 8, 54 R252 Graffiti Remover Viscous 14 TG7205 WR2 Calcium Grease 42 IS5 Mould Release Medium 26 R208 Metal Working Spray 23, 49 R253 Hard Surface Foam Cleaner 14 TG7204 WR2 Calcium Grease 42 IS60 Clear Mould Protector 33 R209 Graphited Penetrating Oil 19 R254 High Wax Polish 14 TG7304 High Speed Grease 2 42 IS60 Clear Mould Protector 33 R210 Heavy Duty Adhesive 28 R255 Ink & Gum Remover Citrus Based 14 TG7505 Iz CgP Lithium Grease 44 IS75 Clear Fork Lift Chain Lubricant 20 R211 Clear Fine Oil 19 R257 Upholstery Foam Cleaner 15 TG7625 Chassis Grease 000 41 IS77 Synthetic Chain Lubricant 20 R212 Clear Penetrating Oil 19 R258 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 IS9 Mould Release Light 26 R213 Water Displacing Anti Rust Agent 19, 53 R260 Heavy Duty Adhesive 28 TG7818 BE-100 Rope Lubricant 00 42 Non-Chlorinated 15 TG805 Nickel Anti-Seize Compound 51 IS92 Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 R261 Super Power Air Freshener Cranberry 13 TG805 Aluminium Anti-Seize 51 IS93 Crack Detector Developer No. 2 28 R215 Belt Dressing Anti-Slip 21 R262 Chewing Gum Remover 16 TG805 Copper Anti-Seize Compound 51 ILMBE Line Marker Blue 37 R217 Silicone Lubricant 22 R266 Green Moisture Guard 33 Islands 33 Islands 33 R200 R250 Anti-Static Cleaner 17 TG805 Islands 33 Islands 34	IS3	De-Watering, Anti-Rust	19, 53	R204	Battery Terminal Protector	33	R249	Air Freshener Lemon	13	TG6004	Lithium PB Advanced	45
IS45 Synthetic Ejector Pin Lubricant 26 R207 Industrial Cleaner Fast Drying 8, 54 R252 Graffiti Remover Viscous 14 TG7205 WR2 Calcium Grease 42 MR2 Calcium Grease 2 42 MR2 Calcium Grease 42 MR2 Calcium		Tool Protector		R205	Dashboard Renovator Cranberry	7	R250	Barrier Cream	14	TG6301	SILIXIS+	40
ISS Mould Release Medium 26 R208 Metal Working Spray 23, 49 R253 Hard Surface Foam Cleaner 14 TG7304 High Speed Grease 2 42 R250 Clear Mould Protector 33 R209 Graphited Penetrating Oil 19 R254 High Wax Polish 14 TG7412 Electrical Conductive Compound 41 R257 Clear Fork Lift Chain Lubricant 20 R211 Clear Fine Oil 19 R257 Upholstery Foam Cleaner 15 TG7625 Chassis Grease 000 41 R257 Synthetic Chain Lubricant 20 R212 Clear Penetrating Oil 19 R258 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 R260 Heavy Duty Adhesive 28 R250 Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 R260 Heavy Duty Adhesive 28 R215 Belt Dressing Anti-Slip 21 R262 Chewing Gum Remover Citrus Based 14 TG7550 L2 GP Lithium Grease 44 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Grease 000 41 TG7550 L2 GP Lithium Grease 45 TG7625 Chassis Greas	IS35	Ceramic Release Spray	23, 49	R206	Dashboard Renovator Lemon	7	R251	Graffiti Remover	14	TG7204	WR2 Calcium Grease	42
ISO Clear Mould Protector 33 R209 Graphited Penetrating Oil 19 R254 High Wax Polish 14 TG7412 Electrical Conductive Compound 41 ISTO Green Mould Protector 33 R210 Heavy Duty Adhesive 28 R255 Ink & Gum Remover Citrus Based 14 TG7550 L2 GP Lithium Grease 44 ISTO Clear Fork Lift Chain Lubricant 20 R211 Clear Fine Oil 19 R257 Upholstery Foam Cleaner 15 TG7625 Chassis Grease 000 41 ISTO Synthetic Chain Lubricant 20 R212 Clear Penetrating Oil 19 R258 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 ISTO Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 ISTO Crack Detector Red Dye No. 2 28 R215 Belt Dressing Anti-Slip 21 ISTO Crack Detector Developer No. 3 28 R216 Open Gear Lubricant 21 R262 Chewing Gum Remover 16 TG8205 Copper Anti-Seize Compound 51	IS45	Synthetic Ejector Pin Lubricant	26	R207	Industrial Cleaner Fast Drying	8, 54	R252	Graffiti Remover Viscous	14	TG7205	WR2 Calcium Grease	42
IS70 Green Mould Protector 33 R210 Heavy Duty Adhesive 28 R255 Ink & Gum Remover Citrus Based 14 TG7550 L2 GP Lithium Grease 44 Inches Ink & Gum Remover Citrus Based 14 TG7550 L2 GP Lithium Grease 44 Ink & Gum Remover Citrus Based 15 TG7550 L2 GP Lithium Grease 44 Ink & Gum Remover Citrus Based 16 TG7550 L2 GP Lithium Grease 45 Ink & Gum Remover Citrus Based 16 TG7550 L2 GP Lithium Grease 46 Ink & Gum Remover Citrus Based 17 TG7550 L2 GP Lithium Grease 47 Ink & Gum Remover Citrus Based 18 TG7550 L2 GP Lithium Grease 48 Ink & Gum Remover Citrus Based 19 TG7550 L2 GP Lithium Grease 49 Ink & Gum Remover Citrus Based 19 TG7550 L2 GP Lithium Grease 49 Ink & Gum Remover Citrus Based 19 TG7550 L2 GP Lithium Grease 49 Ink & Gum Remover 15 TG7712 Heavy Duty Open Gear Grease 41 Ink & Gum Remover 19 TG7712	IS5	Mould Release Medium	26	R208	Metal Working Spray	23, 49	R253	Hard Surface Foam Cleaner	14	TG7304	High Speed Grease 2	42
IS75 Clear Fork Lift Chain Lubricant 20 R211 Clear Fine Oil 19 R257 Upholstery Foam Cleaner 15 TG7625 Chassis Grease 000 41 Stainless Chain Lubricant 20 R212 Clear Penetrating Oil 19 R258 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 Material Displacing Anti Rust Agent 19, 53 R260 Heavy Duty Adhesive Non-Chlorinated 15 TG7712 Heavy Duty Open Gear Grease 41 Non-Chlorinated 17 TG8005 Nickel Anti-Seize Compound 51 Non-Chlorinated 17 TG8005 Nickel Anti-Seize Compound 51 TG8105 Aluminium Anti-Seize 51 TG8105 Aluminium Anti-Seize 51 TG8205 Copper Anti-Seize Compound 51 TG8205 Copper	IS60	Clear Mould Protector	33	R209	Graphited Penetrating Oil	19	R254	High Wax Polish	14	TG7412	Electrical Conductive Compound	41
IS77 Synthetic Chain Lubricant 20 R212 Clear Penetrating Oil 19 R258 Stainless Steel Cleaner 15 TG7712 Heavy Duty Open Gear Grease 41 Mon-Chlorinated 19 Non-Chlorinated 19 Non-Chlorina	IS70	Green Mould Protector	33	R210	Heavy Duty Adhesive	28	R255	Ink & Gum Remover Citrus Based	14	TG7550	L2 GP Lithium Grease	44
IS9 Mould Release Light 26 R213 Water Displacing Anti Rust Agent 19, 53 IS91 Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 IS92 Crack Detector Red Dye No. 2 28 R215 Belt Dressing Anti-Slip 21 R262 Chewing Gum Remover 16 R262 Chewing Gum Remover 16 R265 Anti-Static Cleaner 17 TG805 Copper Anti-Seize Compound 51 TG8205 Cop	IS75	Clear Fork Lift Chain Lubricant	20	R211	Clear Fine Oil	19	R257	Upholstery Foam Cleaner	15	TG7625	Chassis Grease 000	41
IS91 Crack Detector Cleaner No. 1 28 R214 Cutting & Tapping Fluid 23, 49 IS92 Crack Detector Red Dye No. 2 28 R215 Belt Dressing Anti-Slip 21 IS93 Crack Detector Developer No. 3 28 R216 Open Gear Lubricant 21 LMBE Line Marker Blue 37 R217 Silicone Lubricant 22 R266 Anti-Static Cleaner 17 R276 Super Power Air Freshener Cranberry 13 R267 Chewing Gum Remover 16 R268 Anti-Static Cleaner 17 R268 Fe-Too Robe Lubricant 00 42 TG8005 Nickel Anti-Seize Compound 51 TG8105 Aluminium Anti-Seize 51 R269 Copper Anti-Seize Compound 51 TG8205 Copper Anti-Seize Compound 51 TG8205 Copper Anti-Seize Compound 51 TG8205 Copper Anti-Seize Compound 51 TG8304 Lithium Moly Grease 44	IS77	Synthetic Chain Lubricant	20	R212	Clear Penetrating Oil	19	R258	Stainless Steel Cleaner	15	TG7712	Heavy Duty Open Gear Grease	41
IS92 Crack Detector Red Dye No. 2 28 R215 Belt Dressing Anti-Slip 21 R262 Chewing Gum Remover 16 R265 Anti-Static Cleaner 17 TG8205 Copper Anti-Seize Compound 51 TG8205 Nickel Anti-Seize Compound 51 TG8205 Nickel Anti-Seize Compound 51 TG8205 Copper Anti-Seize Compound	IS9	Mould Release Light	26	R213	Water Displacing Anti Rust Agent	19, 53	R260	· · · · ·	28	TG7818	BE-100 Rope Lubricant 00	42
IS93 Crack Detector Developer No. 3 28 R216 Open Gear Lubricant 21 R262 Chewing Gum Remover 16 TG8105 Aluminium Anti-Seize 51 TG8205 Copper Anti-Seize Compound 51 R265 Anti-Static Cleaner 17 TG8205 Copper Anti-Seize Compound 51 TG8304 Lithium Moly Grease 44 R266 Green Moisture Guard 33	IS91	Crack Detector Cleaner No. 1	28	R214	Cutting & Tapping Fluid	23, 49				TG8005	Nickel Anti-Seize Compound	51
LMBE Line Marker Blue 37 R217 Silicone Lubricant 22 R265 Anti-Static Cleaner 17 TG8304 Lithium Moly Grease 44	IS92	Crack Detector Red Dye No. 2	28	R215	Belt Dressing Anti-Slip	21		· ·	′	TG8105	Aluminium Anti-Seize	51
LMBE Line Marker Blue 37 R217 Silicone Lubricant 22 R265 Anti-Static Cleaner 17 TG8304 Lithium Moly Grease 44	IS93	Crack Detector Developer No. 3	28	R216	Open Gear Lubricant	21				TG8205	Copper Anti-Seize Compound	51
LMBK Line Marker Black 37 R218 Moly Dry Film Lubricant 22 R266 Green Moisture Guard 33 TG8305 Lithium Moly Grease 44	LMBE	Line Marker Blue	37	R217	Silicone Lubricant	22				TG8304		44
	LMBK	Line Marker Black	37	R218	Moly Dry Film Lubricant	22	R266	Green Moisture Guard	33	TG8305	Lithium Moly Grease	44

Code Des	scription	Page
TG8312	Lithium Moly Grease	44
TG8404	EP2 Lithium Grease	45
TG8405	EP2 Lithium Grease	45
TG8412	EP2 Lithium Grease	45
TG8418	EP2 Lithium Grease	45
TG8430	EP2 Lithium Grease	45
TG8430W	White Lithium Grease	46
TG8450	EP2 Lithium Grease	45
TG8504	High Temperature Grease	42
TG8605	Silicone Paste	43
TG8620	Silicone Paste	43
TG8630	Silicone Valve Seal	43
TG8650	Silicone Paste	43
TG8704	Very High Temperature Grease	42
TG8730	Very High Temperature Grease	42
TG8804	EP3 Lithium Grease	45
TG8812	EP3 Lithium Grease	45
TG8904	Blue Lithium Complex Grease	46
TG8905	Blue Lithium Complex Grease	46
TG8912	Blue Lithium Complex Grease	46
TG9004	Red Lithium Complex Grease	46
TG9012	Red Lithium Complex Grease	46
TG9112	Wire Rope Grease 000	42
TG9212	EPO EPO/EP00/EP000 Lithium Grease	e 45
TG9312	EP00 EP0/EP00/EP000 Lithium Grea	se 45
TG9412	EP000 EP0/EP00/EP000 Lithium Gre	ase 45
TG9718	Winch Gear Low Temp Grease	41
TG9804	Calcium Sulphonate Grease	41
TG9805	Water Resistant Hub Grease	41
TG9818	Calcium Sulphonate Grease	41
TGG502	Premium Side Lever Grease Gun	56
TGG503	Premium Pistol Grip Grease Gun	57
TGG506	Clear Vision Lever Grease Gun	57
TGG507	Clear Vision Pistol Grip Grease Gun	57
TGG508	Flexible Extension	57
TGG509	Flexible Extension	57
TGG510	Hydraulic 4 Jaw Grease Gun Couple	
TGG511	Refillable Auto Bearing Lubricator	57
TGG512	Refillable Auto Bearing Lubricator	57
TGG513	Grease Nipple Assortment Pack	57
TGG514	Grease Nipple Assortment Pack	57
TGG521	Hand Operated Oil Pump	57

Glossary of Terms

ISO9001:2008

Internationally recognised Quality Management System which has been implemented and maintained by TYGRIS since 2004.

ISO14001: 2004

Internationally recognised Environmental Management System to assist in controlling the environmental impact of a company's activities.

NSF International

Formerly the National Sanitation Foundation, NSF launched its voluntary Nonfood Compounds Registration Programme to re-introduce the previous authorisation programme administered by the U.S. Department of Agriculture (USDA). Product evaluation is based on formulation and label review.

InS Services (UK based, operational worldwide)

InS has been in operation since 2008. It operates a programme for the registration of Nonfood Compounds to the standards originally set out by the U.S. Food & Drugs Administration (FDA) and administered by the US Department of Agriculture (USDA). In 1998 this was administered by NSF International and in 2008 InS introduced a fast web-based alternative, operating to the same standards and with published prices.

3H

Proprietary substances for use as a release agent and acceptable for direct food contact. These products are used on grills, loaf pans, cutters, boning benches, chopping boards, or other hard surfaces in contact with meat and poultry food products to prevent food from adhering during processing. Products containing edible oils such as corn oil, cottonseed oil and soybean oil, mineral oil complying with 21 CFR, Part 172, Section 172.878, and other GRAS substances may be acceptable upon review by NSF. In addition, defoaming agents complying with 21 CFR Section 173.340 (a) (1) and (a) (2) may be acceptable.

Nonfood Compounds

Products that are used in and around food processing areas, but are not intended for direct food contact, or are not expected to become a component of a meat, poultry, or egg product, are defined as "nonfood compounds". These include products such as maintenance and cleaning chemicals, sanitizers and pesticide chemicals, lubricants, water treatment compounds, shell egg cleaning, defoaming, destaining, and sanitizing compounds, and other miscellaneous products.

Nonfood Compounds Programme categories listed in this guide:

A1 – Compounds for use as general cleaning agents on all surfaces, or for use with steam or mechanical cleaning devices in all departments. Before using these compounds, food products and packaging materials must be removed from the room or carefully protected. After using these compounds, surfaces must be thoroughly rinsed with potable water.

A7 - Metal cleaners and polishes for nonfood contact surfaces

These compounds must be used in a manner so that all odours associated with the compounds are dissipated before food products or packaging materials are re-exposed in the area.

H1 - Lubricants with incidental contact

These compounds may be used as a lubricant with incidental food contact for use in official establishments operating under the Federal meat and poultry products inspection programme. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compounds must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food by being processed.

K1 – Cleaning and/or degreasing solvents for use in non-processing areas

Following the use of these compounds, equipment and utensils must be thoroughly washed, and rinsed with potable water, before being returned to a processing area.

K2 - Solvents for cleaning electronic instruments

These compounds are chemically acceptable for cleaning electronic instruments and devices which will not tolerate aqueous cleaning solutions. Before using these compounds,

food products and packaging materials must be removed from the area or carefully protected. These compounds must be used in a manner so that all odours associated with the compound are dissipated before food products or packaging materials are in the area.

K3 – Adhesives or glue removers

Before using these compounds, food products and packaging materials must be removed from the area or carefully protected. After using these compounds, all surfaces must be thoroughly washed and rinsed with potable water. These compounds must be used in a manner so that all odours associated with the compound are dissipated before food products or packaging materials are re-exposed in the area.

REACH

REACH is a European Union regulation concerning the Registration, Evaluation, Authorisation & Restriction of Chemicals. It came into force on the 1st of June 2007 and replaces a number of European Directives and Regulations with a single system.

Can't find the right product?

Online product search www.tygrisindustrial.com

Talk to TYGRIS **01294 311066**

